

MORTAFLEX PLUS

POWDER PLASTICISER FOR BRICK AND
BLOCK LAYING AND PLASTERING



DESCRIPTION:

MORTAFLEX PLUS is a highly concentrated powder that will plasticise, increase open time, retain water, help prevent efflorescence, shrinking and cracking, reduce water absorption and increase bond and strength.

MORTAFLEX PLUS will improve workability, giving a fatter mix and without the necessity of rewetting.

Can be used with all coloured mortar including black oxide. Low cost per mix. Do not use with lime. If lime is required in mix, use CEMPLUS PLASTICISER

MIXING INSTRUCTIONS:

MORTAFLEX PLUS is ideally added to the bowl during mixing. Shake container thoroughly before use.

Use 3 level measuring caps (12 gms per cap) per 40kg bag of cement (measuring cap provided in container).

Amount of plasticiser required may vary with the type of sand used, however it is important not to overdose or overmix. As MORTAFLEX PLUS acts as a water reducer you may require less water to achieve a workable mix.

DO NOT overmix, a maximum of 3 minutes is suggested for most sands.

As a guide the following mortar formula is provided as a starting point.

Mix 6 or 7 parts by volume of good clean sand to 2 parts ordinary cement. Add MORTAFLEX PLUS as per instructions. Mix with clean water to desired consistency.

SHAKE WELL BEFORE USE

PACKAGING:

200gms Plastic Jar – will plasticise 5 bags of cement

600gms Plastic Jar – 15 bags

1.5kg Plastic Jar – 37 bags

3.0kg Plastic Jar – 75 bags

6.0kg Plastic jar – 150 bags

PRECAUTIONS:

MORTAFLEX PLUS should be kept away from children. Not to be ingested or inhaled. Mild irritant. Non-toxic
For large commercial applications and additional info please contact us at 0800 ASK CEMIX

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.