

DATA SHEET

Masonry Mortar Mix

Grey Waterproof



DESCRIPTION

MASONRY MORTAR STANDARD GREY WATERPROOF is ideal for waterproofing all types of dry brick and block masonry joints work. The mortar displays a high level of workability and coverage, especially suited for professional brick/block layers.

RECOMMENDED USE

It is generally used for:

- Water proof brick and block mortar jointing
- To prevent any water penetration into the substrate through the mortar joints of any waterproof brick and block walls

COMPOSITION & MATERIALS

MASONRY MORTAR STANDARD GREY WATERPROOF consists of a uniformly blended, properly proportioned mixture of sands, Portland cement and other admixtures approved for use in waterproof mortar. MASONRY MORTAR STANDARD GREY WATERPROOF has waterproofing additives in addition to the other additives in the CEMIX MORTAR MIX TO improve workability and performance of the product.

PACKAGING

- 30kg bags
- Bulk bags available

YIELD

Under ideal conditions, one 30kg bag is enough to lay 45 clay bricks and 25 concrete blocks.

DIRECTIONS FOR USE

1. Empty contents into a wheelbarrow, mechanical mixer or onto a smooth non-porous surface.
2. Add water gradually, mixing thoroughly until a smooth mix is achieved. Do not over mix. Under ideal conditions a bag of 30kg would require approx 4.5 - 5 litres of water.
3. Damp the clay bricks before laying them. Concrete blocks should be laid relatively dry.
4. Place a layer 15 - 20 mm of mortar between layers of bricks/blocks. The joint gaps are usually 10 - 15mm.
5. Pointing is easier after the mortar has initially set.

TECHNICAL DATA

Complies with NZS 4210; 1989 for Masonry Construction.

STORAGE

Store all cement products in a cool dry area and use within 6 months.

WARNINGS

HAZARDOUS - PORTLAND AND BLENDED CEMENT

This product may contain Crystalline Silica.

RISK

Cements may cause respiratory, skin and eye irritation. Wet cement can be irritating and corrosive to eyes and skin; and may cause skin sensitization (dermatitis). Repeated inhalation may cause bronchitis, silicosis and lung cancer and increase risk of scleroderma.

SAFETY: Avoid contact with eyes and skin, both from wet and dry

mix. Do not breathe in dust. Wear suitable protective clothing, gloves, eye protection and barrier cream. Wear a suitable dust mask. Wash thoroughly after handling and properly store any leftover material.

FIRST AID: Irrigate eyes with plenty of water and seek medical advice immediately.

SPILLS AND LEAKS: Keep out of sewers and stormwater drains and dispose of any leftover material as trade waste in accordance with local authority guidelines. Additional information can be had from the brochures or by calling 0800 ASK CEMIX.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.

CEMIX