

AQUASTOP

CEMENT BASED WATERPROOF SLURRY COATING SYSTEM



DESCRIPTION:

AQUASTOP is a cement based powder and when mixed with the required amount of water, can be applied with brush, smooth roller, sprayed or trowelled to any correctly prepared concrete or masonry surface.

AQUASTOP is recommended as a very effective, decorative waterproofing coating on interior or exterior concrete, masonry, concrete block, mortar, plaster, stucco and brick. It cannot be applied over bitumen, tar, oil, rubber, plastic, metal etc. surfaces or previously painted concrete surfaces.

ADVANTAGES:

- Resists hydrostatic pressure to the interior surface.
- Can be applied to a damp surface.
- Chemically bonds to the surface and will not chalk or dust.
- Does not support mould or fungus growth.
- Finishes white but can be tinted with oxide or painted.
- Provides a water repellent surface which will withstand a head of water from the opposite side of the structure.

DIRECTIONS:

SURFACE PREPARATIONS:

All loose particles, dust, dirt, oil and surface debris must be removed. As a filler, mix one part AQUASTOP with two parts clean sand and mix with a little water. Use for larger cracks, hollows etc. If necessary the whole area should be water blasted to ensure perfect preparation.

MIXING:

To clean water slowly pour in the AQUASTOP powder while stirring constantly with a flat stick to a smooth and creamy (paint like) consistency. Allow to stand for 10 minutes, stir before applying and stir occasionally while using to prevent settling. AQUASTOP must be applied within two hours of mixing. Apply to the predampened surface thoroughly and evenly ensuring any air bubbles/pin holes are brushed out.

Two coats are recommended for exterior surfaces and below ground level interior surfaces where hydrostatic pressure is to be contained. The second coat may be applied any time 6 hours after the first coat.

Do not apply outside if rain is expected during or immediately after application. High winds, direct sunlight or excessive heat may cause AQUASTOP to cure too quickly. It is recommended to paint exterior work while it is shaded.

COVERAGE:

First coat on concrete block or similar surface 2 - 3 sqm per kg.
First coat on stucco and rough surfaces 1.5 - 2.5 sqm per kg.
Second coat on concrete block or similar 3.5 - 4.5 sqm per kg.
Second coat on stucco or similar 3.0 - 4.0 sqm per kg.

PACKAGING:

AQUASTOP is packed in 2kg, 4kg, 10kg and 20kg plastic pails.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.

Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.