



# CEMIX BITUPROOF PLUS

BITUMEN WATERPROOFING MEMBRANE FOR CONCRETE,  
BLOCKS, BRICKS, WOOD & METAL

## NEW ADVANCED FORMULA

Conforms to NZS 3604:1999 &  
Complies with NZ Building Code Clause  
E2/AS1

### DESCRIPTION:

BITUPROOF is a specially formulated stable bituminous emulsion for sealing and waterproofing concrete and concrete block walls below and above ground. It is equally suited for waterproofing and damp-proofing applications on practically any type of surface, vertical or horizontal.

### ADVANTAGES:

- Will bond to almost any surface.
- Does not run or creep under any heat.
- Can be applied to damp surfaces.
- Resists a wide range of acids and alkalis.
- Odourless and produces no fumes.
- Can be sand filled to produce a mortar.

### USES:

BITUPROOF is specially designed for waterproofing applications and will bond to almost any surface. BITUPROOF PLUS may be applied to new or existing structures, and will bond to a damp surface. Can also be mixed with sand, to form a mortar of any desired consistency.

### APPLICATION:

To most surfaces, apply BITUPROOF PLUS as supplied, by brush. The first coat should be applied in one direction only. If possible the second coat should be applied at right angles to the first.  
**DO NOT BRUSH OUT TO OBTAIN BETTER COVERAGE.**

Two coats of BITUPROOF PLUS are recommended for complete waterproofing. BITUPROOF PLUS is an air setting material, and will dry on brushes during

application. It is suggested that the brushes be washed out every 15 - 20 minutes. For large areas, 2 or 3 brushes used in rotation can help to reduce loss of time during application. Final clean up should be carried out using white spirits or similar materials.

When used as a sand mortar, the amount of sand added to the BITUPROOF PLUS will determine the plasticity of the mortar and the hardness of the set material.

### CAUTION:

Bituminous products will deteriorate under ultra-violet light. BITUPROOF PLUS may be protected from such damage by painting with water based paints. Consult paint manufacturers regarding method of application and suitability of paint for use over bituminous coatings.

### WARNING:

Protect from frost during storage.

### COVERAGE:

1 - 2 square metres per litre per coat. Coverage depends on the texture of the surface being treated and the thickness at which the material is applied.

### PACKAGING:

BITUPROOFPLUS is packed in 2 litre, 4 litre and 20 litre pails and 210 litre drums.

### DISCLAIMER

*Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.*

*Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.*

