

SPECIFICATION DATA SHEET

CEMPLASTER™ (CPL025)



DESCRIPTION:

CEMPLASTER can be used for plastering over lath wall, block work, brick work and tilt slab substrates. CEMPLASTER displays a high level of workability and coverage, it resists sagging, cracking and shrinkage. The results of CEMPLASTER are assured only if it is applied on a key coat of CEMSPLASH.

RECOMMENDED USES

It is generally used for:

- Applications where a solid wall plaster in layers up to 12mm are required.
- CEMPLASTER is especially suited for professional plasterers.

COMPOSITION & MATERIALS

CEMPLASTER consists of a uniformly blended, properly proportioned mixture of sands, portland cement and other admixtures approved for use in mortar to improve water retention, workability and performance of the product.

PACKAGING

- 30kg bags
- Bulk bags available

YIELD

Under ideal conditions one 30kg bag will cover 2.4m² approx at 10mm - 12mm thickness.

DIRECTIONS FOR USE

1. Please ensure that CEMSPLASH has been applied to the substrate to be plastered, and that key coat has been given at least 48 hours to cure and harden.
2. Empty contents of CEMPLASTER bag into a mechanical mixer .
3. Add water gradually, mixing until a smooth mix is achieved. Under ideal conditions a bag of 30kg would require approx 4.5 - 5 litres of water.
4. Mix only until you get the desired consistency and don't over mix.
5. Pour in a barrow and then apply. Prior to applying CEMPLASTER please ensure the key coat is moist enough.
6. Do not let the mix stand unused for long periods of time.
7. Depending on the weather, please ensure that the surface is kept moist for 7 days.

TECHNICAL DATA

Complies with NZS 3113/ NZS3103/ NZS 4251 for Plastering.

STORAGE

Store all cement products in a cool dry area and use within 6 months.

WARNINGS

HAZARDOUS - PORTLAND AND BLENDED CEMENT

This product may contain Crystalline Silica.

RISK: Cements may cause respiratory, skin and eye irritation. Wet cement can be irritating and corrosive to eyes and skin; and may cause skin sensitization (dermatitis). Repeated inhalation may cause bronchitis, silicosis and lung cancer and increase risk of scleroderma.

SAFETY: Avoid contact with eyes and skin, both from wet and dry mix. Do not breathe in dust. Wear suitable protective clothing, gloves, eye protection and barrier cream. Wear a suitable dust mask. Wash thoroughly after handling and properly store any leftover material.

FIRST AID: Irrigate eyes with plenty of water and seek medical advice immediately.

SPILLS AND LEAKS: Keep out of sewers and stormwater drains and dispose of any leftover material as trade waste in accordance with local authority guidelines. Additional information can be had from the brochures or by calling 0800 ASK CEMIX.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.