

SPECIFICATION DATA SHEET

CEMPLUS™

CONCENTRATED PLASTICISER FOR MORTAR AND PLASTER



USES:

A very active non-staining liquid which readily mixes with water to improve the workability and adhesion of cement mortar and plaster. Eliminates the need for hydrated lime, but can be used with lime if required. A great masonry aid for laying bricks, concrete blocks and stone. Absolutely essential for solid plastering.

ADVANTAGES:

- Increases bond strength.
- Quicker application.
- Easier working.
- Greater plasticity.
- Cleaner work, less droppings.
- Easier ruling off.
- Reduces cracks and crazing.
- Cuts costs – increases productivity.
- Eliminates need for lime.
- Reduces water absorption.
- Resists freeze – thaw damage.
- Economical – fraction the price of plasticising paste.
- Helps prevent efflorescence.

INSTRUCTIONS FOR USE:

Agitate contents before using. For normal soft sand, add up to 80 millilitres of CEMPLUS per 40kg bag of cement. For harsh, sharp or gritty sand up to a maximum of 120 millilitres per 40kg bag of cement may be required. It is important not to use too much CEMPLUS as this will cause over aeration which will weaken the mortar. Mix the sand and cement in the desired amounts. Add CEMPLUS to the mixing water proportionate to the above dosage and add to the mixing bowl. The more the mix is worked the fatter it becomes. Accurate measuring is essential as too much CEMPLUS will affect the mix. Use less rather than more.

PACKAGING:

CEMPLUS is packed in 1 litre, 2.5 litre and 5 litre bottles, 20 litre pail/jerry can and 210 litre drum.

PRECAUTIONS:

CEMPLUS is non-toxic and non-flammable. Should it be splashed into the eyes, wash eyes immediately and seek medical attention. It should not be ingested, but if it is again seek medical attention. Prolonged skin contact should be avoided.

TECHNICAL SERVICE:

For your nearest stockist or additional technical information for CEMPLUS or any other of our wide range of adhesives, sealing compounds, concrete admixtures and other additives for the construction industry, contact CEMIX PRODUCTS LTD.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.

Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.