

C.F.R.A.

CONCRETE FORMWARE RELEASE AGENT



DESCRIPTION:

C.F.R.A. is a formwork release agent which is applied to the inner face of shuttering, formwork and moulds, before the casting of concrete. C.F.R.A. is used to break the bond and allow an easy release between the cast concrete and formwork. May also be used to stop the build-up of concrete on tools, handling equipment and machinery. C.F.R.A. does not stain concrete.

ADVANTAGES:

- Easy bond breaking.
- Easy stripping of forms.
- Smooth, stain free concrete.
- Can safely be used on tools etc.

USES:

Spray or paint a thin coating of C.F.R.A. on to the casting face of all forming before each pour or cast of concrete. Apply to the backs and sides of all forming at regular intervals to allow for easy cleaning. The regular use of C.F.R.A. on timber forming lowers maintenance costs and increases the effective life as well as producing a waterproof coating.

CAUTION:

Care must be taken to avoid applying THICK coatings to NEW hardboard or plywood forming, as this could cause damage to the surface finish.

C.F.R.A. must not be allowed to come into contact with any reinforcement, as it stops the concrete from bonding to the steel.

C.F.R.A. causes a dust film where it touches the concrete surface. This film must be brushed away before any other work contacting the concrete surface is carried out.

APPLICATION:

C.F.R.A. is supplied ready for use, no thinning necessary. Apply by brush or spray, a thin coating of C.F.R.A.

to wooden or steel shuttering formwork or moulds before each concrete cast. For plant, handling equipment and machinery etc., hose clean and spray with C.F.R.A. at the end of work. For hand tools, buckets etc. simply soak in the container of C.F.R.A. and allow to dry.

THOROUGHLY AGITATE CONTENTS BEFORE USE

COVERAGE:

C.F.R.A. covers up to 20sqm per litre when sprayed with suitable equipment.

PACKAGING:

C. F.R.A. is packed in 4 litre pails, 20 litre metal cans and 210 litre drums.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.

Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.