

DATA SHEET

Cemplash™ (CSP025)**PRODUCT DESCRIPTION**

CEMSPLASH is a rapid (key coat). It forms an excellent key for application of solid wall plaster 12mm and above. This can be used on certain painted substrates, but please contact a CEMIX representative for guidance.

RECOMMENDED USE

It is generally used for:

- Application over block work, brick work and other bare concrete substrates.

COMPOSITION & MATERIALS

CEMSPLASH consists of a uniformly blended, properly proportioned mixture of sands, Portland cement and other admixtures which promote bond to the substrate.

PACKAGING

- 25kg bags
- Bulk bags available

YIELD

Under ideal conditions a 25kg bag will yield approximately 5m².

DIRECTIONS FOR USE

1. Please ensure that the surface is free from all loose, weak friable materials, oil, grease, dirt, moss, mould and any other thing that can inhibit bond. Mechanical preparation techniques for old walls are preferred.
2. Empty contents into a mechanical mixer. Add water gradually, mixing until a smooth desired consistency is achieved. Under ideal conditions a bag of 25kg would require approx 5 - 6 litres of clean water.
3. Mix only until you get the desired consistency and don't over mix.
4. Pour in a bucket and then apply using a flat dashing trowel/splash trowel. Continue mixing the contents of the bucket as you splash onto the wall.
5. Do not let the mix stand unused for long periods of time.
6. Cure the applied coat with a spray of water, after 24 hours and 48 hours. Thereafter apply CEMPLASTER, thus giving the key coat a minimum of 48 hours to harden properly.

TECHNICAL DATA

Complies with NZS 3113/ NZS3103/ NZS 4251 for plastering.

STORAGE

Store all cement products in a cool dry area and use within 6 months.

WARNINGS

HAZARDOUS - PORTLAND AND BLENDED CEMENT
This product may contain Crystalline Silica.

RISK

Cements may cause respiratory, skin and eye irritation. Wet cement can be irritating and corrosive to eyes and skin; and may cause skin sensitization (dermatitis). Repeated inhalation may cause bronchitis, silicosis and lung cancer and increase risk of scleroderma.

SAFETY

Avoid contact with eyes and skin, both from wet and dry mix. Do not breathe in dust. Wear suitable protective clothing, gloves, eye protection and barrier cream. Wear a suitable dust mask. Wash thoroughly after handling and properly store any leftover material.

FIRST AID

Irrigate eyes with plenty of water and seek medical advice immediately.

SPILLS AND LEAKS

Keep out of sewers and stormwater drains and dispose of any leftover material as trade waste in accordance with local authority guidelines. Additional information can be had from the brochures or by calling 0800 ASK CEMIX.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.

DISCLAIMER: