

JOINT SAND™ (PJS040)



DESCRIPTION

JOINT SAND is a scientific formulation of graded sand to allow flexible filling of vertical joints in segmental paving. It forms a flexible joint allowing slight movement of the pavers. It is prepared in a fully computerized environment, where a high degree of accuracy and consistency is maintained.

RECOMMENDED USE

It is generally used for:

- Joint filling and base preparation for pavers, clay tiles and cobbles.
- Any type of paving joint that is not in a high wind and traffic area.

COMPOSITION & MATERIALS

JOINT SAND consists of a uniformly blended, properly proportioned mixture of sands and other additives to improve workability and performance of the product.

PACKAGING

- 40kg bags
- Bulk bags available

YIELD

One 40kg bag of JOINT SAND will cover an area of 12 - 15m², if the paver thickness is 50mm.

DIRECTIONS FOR USE

1. After laying the paving, clean and dry the substrate. Do not apply JOINT SAND to damp pavers.
2. Spread the contents of the bag directly onto the pavers, and use a stiff broom to sweep the contents into the joints.
3. Any product left over the pavers, should be swept clean and then work the entire area with a vibrating plate compactor for a minimum of two passes.
4. Due to the vibration, the JOINT SAND will settle in the joints and some more JOINT SAND might need to be poured over and broomed in to fill those gaps.
5. Compact the entire area again.
6. Apply a light even spray of clean water.
7. For large scale commercial applications, please get in touch with the supplier or CEMIX for advice.

TECHNICAL DATA

Meets NZ standard specification NZS 3116 1991.

STORAGE

Store all cement products in a cool dry area and use within 6 months.

WARNINGS

This product may contain Crystalline Silica.

RISK

Crystalline Silica may cause respiratory, skin and eye irritation. Repeated inhalation may cause bronchitis, silicosis and lung cancer and increase risk of scleroderma.

SAFETY

Avoid contact with eyes and skin, both from wet and dry mix. Do not breathe in dust. Wear suitable protective clothing, gloves, eye protection and barrier cream. Wear a suitable dust mask. Wash thoroughly after handling and properly store any leftover material.

FIRST AID

Irrigate eyes with plenty of water and seek medical advice immediately.

SPILLS AND LEAKS

Keep out of sewers and stormwater drains and dispose of any leftover material as trade waste in accordance with local authority guidelines.

Additional information can be had from the brochures or by calling 0800 ASK CEMIX.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.