

CEMIX SHOWER SEALER

PENETRATING CLEAR WATERPROOFING SEALER



DESCRIPTION

CEMIX SHOWER SEALER is an eco friendly water-based sealer, which penetrates and seals the grout joint of a tiled shower and keeps the shower recess watertight. This prevents moisture traveling into the wall preventing damp problems such as mold growth. Cemix Shower Sealer prevents the grout from collecting dirt, mildew and bacteria resulting in a more hygienic environment. It will not damage the tiles or result in any color change to the grout tile and cement. It is safe to use on all types of tile and

ADVANTAGES

- Environmentally friendly green product
- Makes the substrate water repellent
- Can be applied on damp or moist surfaces
- Hybrid sealer – penetrates as well as coats
- Allows the substrate to breath
- Chemically resistant and non toxic
- UV stable – will not go yellow over time
- Weathering resistant
- Resistant to dirt pick up
- Kills and resists micro-organisms
- Simple application – preferably by roller or spray
- Non toxic
- Fast drying and a clear glossy finish It is advisable to wear the appropriate safety equipment when spraying this product –goggles, respirator and gloves

SURFACE PREPARATION Ideally this sealer should be applied on new freshly laid and cured tiled joints. The surfaces should be made clean, free from grease, loose particles, dirt, paint etc.

APPLICATION Shake or stir thoroughly before use. CEMIX SHOWER SEALER should be applied without diluting in two coats to ensure complete coverage and saturation of the substrate. Application with conventional spray equipment or roller is the preferred method. Depending on the porosity of the substrate – a coverage of 5 square meters per/litre per coat should be achieved. On high absorbent surfaces, repeat or increase the rate of application until surface is completely saturated. Re-

application at a later date is possible provided the substrate is clean.

APPLICATION TEMP: 5°C - 30°C

PACKAGING: 1.2 Lts Spray Pack

PROPERTIES

Type Anionic, Silane Modified Dispersion Appearance Milky, translucent white emulsion

PH - 7.5 to 9.0

Density - @20C 1.06Kg/Lt

Odour - Acrylic

Flash point - Not flammable

Not classified as Dangerous Goods

PRECAUTIONS CEMIX SHOWER SEALER is non-toxic and non-corrosive. If splashed into the eyes, wash eyes with copious amounts of clean water immediately and seek medical attention. If ingested, drink plenty of water and seek medical attention. It is advisable to wear the appropriate safety equipment when spraying this product –goggles, respirator and gloves.

CLEANING: Spray or roller equipment should be washed out immediately after use with water.

STORAGE & SHELF LIFE: Twelve (12) months when stored in unopened, original containers. Storage area should be not exposed to extreme temperatures. Do not expose to direct sunlight in storage.

SAFETY, SPILLS AND LEAKS: Keep out of sewers and storm water and dispose off any leftover as trade waste in accordance with local authority guidelines. Plastic containers can be recycled after a good rinse and thorough wash.

For large commercial applications and additional info please contact us at 0800 ASK CEMIX

DISCLAIMER *Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective*

because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost. Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.