

# TILE & SLATE SEALER

SLATE, CONCRETE AND EXPOSED CONCRETE SEALER



## DESCRIPTION:

A solvent based clear film forming, sealing and dust-proofing coating. Has good flexibility, is long-lasting and will not yellow, crack or peel when properly applied. CEMIX TILE & SLATE SEALER has a positive penetration into the surface.

## USES:

Use CEMIX TILE & SLATE SEALER to enhance the beauty of all types of natural stone, slate, exposed aggregate, concrete and cobblestones. Caution should be used if applying to Terracotta or brick. It is essential that a trial be carried out before proceeding with the full area.

## INSTRUCTIONS:

The surface must be completely dry and thoroughly cleaned of all contaminants and dust before applying CEMIX TILE & SLATE SEALER direct from the container without thinning. Can be applied with brush, roller or spray. Avoid puddles and spread uniformly without brushing out excessively. Two or even three coats may be required depending on the porosity/absorbency of the surface. Allow to dry between coats. Protect the freshly coated surface from dust, rain and traffic while drying. Light traffic may be allowed after 24 hours. Heavy traffic should be avoided for several days; even longer, 7 days, for vehicles. Clean brushes, containers etc. with a general solvent cleaner or thinners.

## IMPORTANT – AGITATE WELL BEFORE USE

### COVERAGE:

CEMIX TILE & SLATE SEALER will cover up to 6 - 10m<sup>2</sup> per/litre per coat. Note: This is an approximate coverage depending on the porosity/absorbency of the surface.

### STORAGE:

CEMIX TILE & SLATE SEALER has a shelf life of 12 months minimum when unopened in original containers.

### PACKAGING:

CEMIX TILE & SLATE SEALER is packed in 1 litre, 2.5 litre and 20 litre plastic pails/jerry cans and 210 litre drums.

### PRECAUTIONS:

CEMIX TILE & SLATE SEALER is flammable and should be used with adequate ventilation. Beware of cigarettes and naked flames near uncovered containers. Keep away from children. Do not splash into eyes. Wash thoroughly with water and seek medical advice immediately. If ingested seek medical advice immediately. Wear suitable protective clothing, gloves and eye/face protection.

## TECHNICAL SERVICE:

For your nearest stockist or additional technical information on CEMIX TILE & SLATE SEALER, or any other of our wide range of adhesives, sealing compounds, concrete admixtures and additives for the construction industry, contact CEMIX PRODUCTS LTD.

## DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost.