

CEMIX UNDERTILE WATERPROOFER

WATERBASED POLYURETHANE ACRYLIC WATERPROOFING MEMBRANE



DESCRIPTION

CEMIX UNDERTILE WATERPROOFER is a water based polyurethane-acrylic non toxic waterproofing membrane designed specially for waterproofing internal/ external wet areas, balconies, decks other areas that needs to be tiled. It is tough, flexible, UV stable when left exposed, environmentally friendly, solvent free, fast drying and excellent adhesion to a wide range of substrates.

ADVANTAGES

- Tough flexible film
- UV stable when left exposed
- Environmentally friendly – solvent free – suitable for confined areas
- Can be tiled over – good adhesion with Cemix tile adhesives
- Fast drying
- Excellent adhesion to a wide range of substrates
- Fast drying
- Easy to apply by brush

SURFACE PREPARATION

Ensure surfaces are dry. Wet concrete should be cured for 28 days and should be allowed to dry thoroughly. Remove all contaminating materials such as dust, oil, paint and curing compounds

APPLICATION

CEMIX UNDERTILE WATERPROOFER should be thoroughly mixed to a uniform mix and ensure the coating is applied by brush or roller evenly at recommended coverage rates The membrane should be 1.0mm thick after 2 coats.

COVERAGE

This will vary with the porosity of the substrate. Two coats are recommended to get optimum performance. CEMIX UNDERTILE WATERPROOFER will cover approximately 1 square metre/ litre on walls or 0.5 square metres per/litre on floors ,based on 2 coats.

DRYING TIME

Recoat once the first coat is totally dry. Drying time under standard conditions is around 4 hours. Do not commence tiling before the membrane is completely dry. This can take upto 48 hours depending on temperature and humidity.

PACKAGING: 1Litre, 4Litres and 20 Litres

PRECAUTIONS

CEMIX UNDERTILE WATERPROOFER is non-toxic and non-corrosive. If splashed into the eyes, wash eyes with copious amounts of clean water immediately and seek medical attention. If ingested, drink plenty of water and seek medical attention. It is advisable to wear the appropriate safety equipment when spraying this product –goggles, respirator and gloves.

CLEANING: Spray or roller equipment should be washed out immediately after use with water.

STORAGE & SHELF LIFE: Twelve (12) months when stored in unopened, original containers. Storage area should be not exposed to extreme temperatures. Do not expose to direct sunlight in storage.

SAFETY, SPILLS AND LEAKS: Keep out of sewers and storm water and dispose off any leftover as trade waste in accordance with local authority guidelines. Plastic containers can be recycled after a good rinse and thorough wash.

For large commercial applications and additional info please contact us at 0800 ASK CEMIX

DISCLAIMER *Other than as appears on this products packaging, CEMIX LTD. does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of CEMIX LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact CEMIX LTD first. If this product is defective because of CEMIX LTD's fault, please contact the supplier or CEMIX LTD. who will replace it at no cost. Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only.*