

EZY TILE

FLEXIBLE WALL & FLOOR ADHESIVE

AVAILABLE SIZE: 8KG & 18 KG

SCAN FOR DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:
Cemix EZY TILE is a flexible, polymer-modified tile adhesive suitable for interior wall and floor tiling. It provides a strong, lasting bond for ceramic, porcelain and mosaic tiles, including larger formats. With excellent slip resistance and extended open time, it's perfect for kitchens, bathrooms and other wet areas. Formulated for professional strength and smooth workability, Cemix EZY TILE delivers reliable results on a wide range of substrates.

ADVANTAGES:
- Strong, flexible bond suitable for walls and floors.
- Excellent slip resistance for secure tile placement.
- Extended open time for easier tile adjustments.
- Suitable for large-format tiles and wet area applications

TYPICAL USES:
- Wall and floor tiling in bathrooms, kitchens, and laundries.
- Ideal for large-format and heavy tiles requiring extra grip.
- Suitable for tiling over concrete or cement-based surfaces.
- Perfect for interior renovation and high-use areas.

SUBSTRATES:
- Concrete, renders & screeds.
- Fibre cement sheet & compressed fibre cement sheet.
- Plasterboard.
- Cemix waterproofing membranes.
- Existing internal ceramic tiles (dry areas only).

COVERAGE:

Pack size	Wall coverage - 6mm notched trowel	Floor coverage - 10mm notched trowel
8kg	Up to 3.2m²	Up to 2.4m²
18kg	Up to 7.2m²	Up to 5.4m²

For detailed information, refer to the Cemix Technical Data Sheet at www.cemix.co.nz

WATER RATIO:
18kg: 5.4 - 5.85L clean water.
8kg: 2.4-2.6L clean water.

PREPARATION:
Ensure all surfaces are clean, dry, and free from dust, grease, or loose material. Clean tiles before fixing to remove dust or residue.

Follow NZS 3114 for best tiling practices. Use a notched trowel to spread adhesive evenly — typically a 6mm trowel for walls and 10mm for floors.

APPLICATION:
1. Spread Cemix EZY TILE to a thickness between 3–10mm.
2. Firmly press each tile into place, sliding slightly across the trowel grooves to achieve full coverage.
3. For tiles with ribbed or textured backs, apply adhesive to both the surface and tile back (back-buttering) for maximum bond.

Lift a tile occasionally to check for full coverage underneath. Avoid spot fixing — ensure complete contact for a strong, durable bond.

DRYING & CURING TIME:
(At 23 °C and 50% humidity – allow longer times for cooler temperatures or dense substrates/tiles.)

- Pot Life: 3 hours
- Trafficable: 24 hours
- Grout Time: 24 hours

Tip: Cemix EZY TILE has an open time of around 30 minutes and an adjustment time of up to 20 minutes, depending on conditions. Only spread as much adhesive as can be tiled before it begins to dry or skin.

GROUTING:
Tiles can be grouted after 24 hours, once the adhesive has fully set and tiles are secure. Allow additional time in cool, damp, or low-ventilation conditions.

Use a suitable Cemix grout for best performance and colour consistency.

EZY TILE

CLEANING:
Clean tools and equipment with water immediately after use.

STORAGE & SHELF LIFE:
Store unopened in a cool, dry place. Shelf life of up to 12 months from the date of manufacture.

PRODUCT LIMITATIONS:
- Not suitable for continuous water immersion (e.g., swimming pools).
- Do not use on metal surfaces or unstable substrates like timber.
- For moisture-sensitive natural stone, seek specialist advice or use Cemix-approved systems.
- For best adhesion and performance, ensure correct water ratio and surface preparation.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARDS:
May cause allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

PREVENTION:
Do not breathe dust/fume. Use only outdoors or in a well- ventilated area. Wear protective gloves, clothing, eye protection, and face protection. Do not eat, drink, or smoke while using this product. Do not handle until all safety precautions have been read and understood. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

RESPONSE:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE (0800 764 766)/doctor/physician/first aider. IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGREDIENTS:
Portland Cement, CAS: 65997-15-1, <40%
Graded Sand, CAS: 14808-60-7, <40%
Calcium Carbonate, CAS: 471-34-1, 25-35%
Calcium formate, CAS: 544-17-2, 10-15%
Cellulose, CAS: 9004-34-6, 5-10%
Ingredients determined not to be hazardous, balance.

DISCLAIMER:
Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

PLEASE REFER TO THE DATASHEET AT WWW.CEMIX.CO.NZ FOR FURTHER INFORMATION AND INSTRUCTIONS.

CEMIX® PRODUCTS LTD
19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ

Twitter/CemixNZ
Facebook/CemixNz
Pintrest/CemixNZ
YouTube/CemixVideos

Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars | Repairs & Grouts | Admixtures | Decorative Sealers | Waterproofing | Tiling & Flooring