



FLOOR LEVELLER

FOR CONCRETE FLOORS AND CEMENT SHEETS

AVAILABLE SIZE: 5kg, 10kg, 20kg



SCAN FOR
DETAILS



WORK TIME



JUST ADD
WATER

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® FLOOR LEVELLER is an easy to use, self levelling, grey cement based compound, designed for levelling concrete flooring surfaces and over tile and slate underlay.

TYPICAL USES:

CEMIX® FLOOR LEVELLER can be used to prepare concrete substrates and cement sheets before the application of flooring materials, including tiles, laminate, vinyl and carpet. Suitable for interior and exterior use.

ADVANTAGES:

- Smooth finish - ideal for the application of vinyl
- Durable finish for use in both domestic and commercial areas

YIELD:

Varies according to the substrate condition.

Approximately 0.2m² per kg of product at a bed thickness of 3mm.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

Smooth surfaces on new and old concrete should be scabbled.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with a CEMIX® bonding agent before the application of CEMIX® FLOOR LEVELLER.

SUBSTRATE TEST:

The concrete substrate must be absorbent or porous. Test this by sprinkling water on the surface. If the water readily soaks into the concrete, the surface is suitable for application. If the water beads on the surface, the concrete is not suitable for application and any previous coatings need to be removed.

MIXING:

1. Add clean water to a mixing container. Use approximately 200ml of water per kg of product.
2. Add CEMIX® FLOOR LEVELLER slowly to the water, mixing constantly with a mixing paddle, until a smooth consistency is achieved.

Note: Only mix as much product as can be used within 20 minutes. Do not aerate the mixture by stirring over vigorously or for too long.

APPLICATION:

1. Pour the mixture onto the surface immediately after mixing it should be in a slurry form.
2. When a screed of uniform bed thickness is required, move it across the surface at a constant speed.
3. Levels may be corrected by applying a greater or lesser amount of mixture.
4. The semi-hardened material may easily be formed or cut, allowing any necessary adjustments to be made.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

FLOOR LEVELLER

CEMIX® FLOOR LEVELLER can be applied at a bed thickness between 3mm to 30mm. Normal application bed thickness is 6mm to 8mm. The product is not self levelling below a bed thickness of 6mm and will need to be manually trowelled to level.

Note: Honour any expansion or control joints.

DRYING & CURING:

Drying and curing time depends on the substrate, substrate condition, climate, the type of application and the materials being applied. Allow a minimum of 24 hours at 20°C, before commencing further work or trafficking.

CLEANING:

Clean tools with water immediately after use. If material becomes set on tools, remove using CEMIX® CONCRETE DISSOLVER.

STORAGE & SHELF LIFE:

Up to 12 months (pail) and 6 months (bag) when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

CEMIX® FLOOR LEVELLER is not self levelling below a bed thickness of 6mm and will need to be manually trowelled to level.

Not to be used on timber flooring.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

**Read label before use. Keep out of reach of children.
If medical advice is needed, have product container or label at hand.**

DANGER



HAZARD STATEMENTS:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. H370 Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

SAFETY INSTRUCTIONS:

Do not breathe dust/fume. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider. Immediately call a POISON CENTER/doctor/physician/first aider. Specific treatment (see advice on this label). IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

INGREDIENTS:

Graded sand, CAS: 14808-60-7, 30-60%
Portland cement, CAS: 65997-15-1, 10-30%
Ingredients determined not to be hazardous, CAS: NA,
Balance

CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

FLOOR LEVELLER

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring