

Nov 2022 | Page 1



NO DAMP WATERPROOFING **ACRYLIC WATERPROOFING MEMBRANE**

AVAILABLE SIZE: 4L



SCAN FOR DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® NO DAMP WATERPROOFING is a grey, acrylic waterproofing membrane, designed for use on a variety of surfaces, including concrete & masonry, in negative pressure applications.

TYPICAL USES:

CEMIX® NO DAMP WATERPROOFING can be used as an interior and exterior waterproofer on concrete, masonry and exterior use plaster surfaces, including:

- Over green, damp or efflorescence prone concrete surfaces, prior to painting or laying timber, carpet, cork, vinyl and ceramic tiles
- Below ground surface applications such as basements. retaining walls and car parks

ADVANTAGES:

· Easy to apply

YIELD:

Varies according to the substrate condition. Approximately 3m² per litre of product, per coat. A minimum of two coats is recommended.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

The substrate should ideally be dry or damp (at most) but not

MIXING:

No mixing required.

APPLICATION:

- 1. Stir before use.
- 2. Apply to the surface generously and evenly, using a roller or medium brush.
- 3. After a minimum of 24 hours, apply a second coat at right angles to the first coat.

DRYING & CURING:

Drying and curing time may vary depending on the substrate and climate. Allow CEMIX® NO DAMP to cure for 24 hours before applying any finishes.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:


Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

Not UV stable.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.



WATERPROOFING

Nov 2022 | Page 2

NO DAMP WATERPROOFING

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of **Dangerous Goods.**

INGREDIENTS:

Vinyl acrylic copolymer, CAS: NA, 30-50% Styrene/ butadiene copolymer, CAS: NA, 10-30% Inorganic mineral filler, CAS: NA, 10-30% Other non hazardous ingredients, CAS: NA, 1-10%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061 AUCKLAND NEW ZEALAND 0800 ASK CEMIX I +64 09 636 1000 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos

