

Nov 2022 | Page 1



ROOF & GUTTER WATERPROOFER

FLEXIBLE RUBBER WATERPROOFING MEMBRANE

AVAILABLE SIZE: 2kg, 4kg, 10kg



DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® ROOF & GUTTER WATERPROOFER is a grey, flexible rubber, UV resistant, waterproofing membrane, designed for use on a variety of surfaces in positive pressure applications.

TYPICAL USES:

CEMIX® ROOF & GUTTER WATERPROOFER can be used as an exterior waterproofer on roofs and gutters, as well as cementitious, metal and timber surfaces. It can be used as a decorative, grey finish. Alternatively, it can be painted over.

ADVANTAGES:

- · Highly flexible
- UV stable
- Can withstand extreme weather conditions

YIELD:

Varies according to the substrate condition.

Approximatlely 2m² per litre of product at a bed thickness of 1.5mm. A minimum of two coats is recommended to achieve this bed thickness.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

The substrate should be dry.

APPLICATION:

- 1. Stir before use.
- 2. Apply to the surface generously and evenly, using a medium
- 3. After a minimum of 4 hours, apply a second coat at right angles to the first coat.

Ensure a bed thickness of 1.5mm is acheived for two coats.

DRYING & CURING:

Drying and curing time may vary depending on the substrate and climate. Drying time is approximately 4 hours. Curing time is approximately 7 days.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:


Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

TECHNICAL DATA:

APPLICATION TEMP.	5°C - 30°C
APPEARANCE	Light grey liquid
POTABLE WATER	Suitable
HYDROSTATIC PRESSURE	Not Suitable

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.





Nov 2022 | Page 2

ROOF & GUTTER WATERPROOFING

LIMITATIONS:

Do not apply if humidity is over 85% or if rain is expected within 48 hours.

Surfaces should have adequate falls.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

WARNING

HAZARD STATEMENTS:

Harmful to aquatic life with long lasting effects. Causes mild skin irritation.

SAFETY INSTRUCTIONS:

Avoid release to the environment.

RESPONSE:

If skin irritation occurs: Get medical advice/attention

INGREDIENTS:

Biocides proprietary; CAS: Not Available, <1% Ingredients determined not to be hazardous; CAS: Not Available, >95%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or

replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN OR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061 AUCKLAND NEW ZEALAND 0800 ASK CEMIX | +64 09 636 1000 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos

