



CEMPLASTER

EXTERIOR USE PLASTER

AVAILABLE SIZE: 20kg | 30kg



SCAN FOR
DETAILS



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® CEMPLASTER is an exterior use plaster used for block and brick work, and concrete substrates, in civil, commercial, industrial and residential applications. The results of CEMIX® CEMPLASTER are only assured when the product is used in conjunction with CEMIX® CEMSPLASH, in accordance with manufacturer's recommendations.

TYPICAL USES:

Used for applications including:

- Brick & Block Work
- Roughcast
- Walls

Note: Specifically designed for external use

ADVANTAGES:

- Ready to use - just add water

COVERAGE:

Approximate coverage per bag:

- 20kg: 1.6m² at a 10mm to 12mm bed thickness
- 30kg: 2.4m² at a 10mm to 12mm bed thickness

STANDARDS:

Complies with NZS 3113, NZS 3103 & NZS 4251

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

All substrates should be structurally sound, securely fastened

and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with CEMIX® CEMSPLASH before the application of CEMIX® CEMPLASTER.

MIXING:

1. Empty the bag contents into a mixing container or mixer.
2. Gradually add the prescribed water, mixing thoroughly until a smooth mix is achieved. Do not over mix.

Bag contents to water ratio:

- 20kg: 3L to 3.4L
- 30kg: 4.5L to 5L

3. Pour into a wheelbarrow.

APPLICATION:

1. Spray the cured coat of CEMIX® CEMSPLASH with clean water first.
2. Apply the mix to the substrate with a plasterer's hawk and trowel.
3. Depending on the weather, ensure that the surface is kept moist for 7 days.

Note: Honour any expansion or control joints.

DRYING & CURING:

Allow to cure for a minimum of 48 hours.

CLEANING:

Clean tools with water immediately after use. If material becomes set on tools, remove using CEMIX® CONCRETE DISSOLVER.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

CONCRETE & MORTARS

Oct 2022 | Page 2

CEMPLASTER

STORAGE & SHELF LIFE:

Up to 6 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

TECHNICAL DATA:

- Appearance: Sand / Cementious
- Application Temp.: 5°C to 30°C

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

LIMITATIONS:

Results are only assured when CEMIX® CEMPLASTER and CEMIX® CEMSPLASH are used in conjunction with each other, in accordance with manufacturer's recommendations.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs
- Causes damage to organs through prolonged or repeated exposure

SAFETY INSTRUCTIONS:

- Obtain special instructions before use
- Do not breathe dust/fume
- Wear protective gloves/protective clothing/eye protection/face protection
- Do not eat, drink or smoke when using this product

- Contaminated work clothing should not be allowed out of the workplace

RESPONSE:

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider. Immediately call a POISON CENTER/doctor/physician/first aider
- IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention

INGREDIENTS:

Silica crystalline - quartz, CAS: 14808-60-7, >60%
Portland cement, CAS: 65997-15-1, 10-30%
Calcium hydroxide, CAS: 1305-62-0, 1-5%
Ingredients determined not to be hazardous, CAS: Not Available, balance

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring