# CEMIX TILE ADHESIVES BPIR DECLARATION



Version 1.0 October 2023

# DESIGNATED BUILDING PRODUCT: Class 1

# DECLARATION

Cemix Products Ltd (Cemix) has provided this declaration to satisfy the provisions of the Building (Building Product Information Requirements) Regulations 2022.

# **COMPANY DETAILS**

Cemix Products Ltd	
Manufacturer Supplier (Pre-mixed Past Adhesive)	
9429031177702	
19 Alfred St, Onehunga, Auckland 1061	
www.cemix.co.nz	
info@cemix.co.nz	
09 636 1000	
	Manufacturer Supplier (Pre-mixed Past Adhesive) 9429031177702 19 Alfred St, Onehunga, Auckland 1061 www.cemix.co.nz info@cemix.co.nz

# **DESCRIPTION OF BUILDING PRODUCT**

Cemix tile adhesives are a range of cement-based tile adhesives. Whilst they all comprise cement and sand (Silica) they also include other additives that provide additional performance characteristics such as level of adhesion, water resistance, flexibility, speed of setting.

With the exception of the Cemix Pre-Mixed Paste Adhesive all are provided in powdered form. These products can be mixed with water or with Tile Latex Bond. Tile Latex Bond is a modified latex additive which improves the adhesion and workability of the adhesive.

Cement-based tile adhesives work by creating a solid adhesive bond between the tile and the substrate (a process known as cement hydration). The additional components within the adhesive ensure durability of this bond by providing performance characteristics such as flexibility and crack resistance.

# SCOPE OF USE

Cemix tile adhesives are intended for the following uses.

# Super Tile Bond, Super Rigid Set & Super Ezybond

Rigid set, high strength adhesive. Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior floor applications.

#### Fast Set Tile Adhesive

Flexible, polymer modified, water resistant. Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting, plasterboard and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior wall and floor applications.

# CEMIX

CEMIX PRODUCTS LTD 19 ALFRED ST, ONEHUNGA, AUCKLAND 1061 | 09 636 1000 | www.cemix.co.nz

Uncontrolled in printed format

#### Floor Tile Adhesive

Flexible, polymer modified, water resistant. Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior floor applications.

# Wall & Floor Tile Adhesive & Wallset White Tile Adhesive

Premium, flexible, polymer modified, water resistant, white.

Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting, plasterboard and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior floor and wall applications.

#### Flexiset

Premium, highly flexible, polymer modified, rubber modified, water resistant. Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior floor applications.

#### Pre-mixed Paste Adhesive

Flexible, water resistant, ready to use. Used for fixing tiles to concrete, cement renders, screeds, fibrous cement sheeting, plasterboard and CEMIX approved waterproofing membranes. Suitable for use in interior and exterior wall and floor applications.

# LIMITATIONS

Cemix tile adhesives are not suitable for,

- tiling directly over flexible substrate i.e. timber, plywood, particleboard, MDF and Masonite etc. or
- use with porcelain tiles, or
- continuous water immersion applications i.e. swimming pools and spas etc.

# **CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS**

The Cemix tile adhesive powder do not have building code obligations. Code contribution arises when mixed and professionally applied to adhere a tile to a wall or floor.

E2 (External Moisture) & E2 (Internal Moisture), applicable performance criteria. Tile adhesives only increase the durability of compliance.

B2 (Durability), B2.3.1(b). The durability of cementitious adhesives is well established in NZ based on in-service use.

F2 (Hazardous Building Materials), F2.3.1. The adhesives are not considered hazardous, and do not emit harmful gases.

# FOR FURTHER INFORMATION

Cemix tile adhesives must be used in accordance with all information supplied by Cemix Products Ltd. For supporting information refer to www.cemix.co.nz

### **RESPONSIBLE PERSON**

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Cemix tile adhesives, as referred to in this statement, are not subject to a warning or ban under s26 of the Building Act.

#### Signed for and on behalf Cemix Products Ltd:

B Dhillon

B Dhillon MANAGING DIRECTOR October 2023

