



WOODEN FLOOR LEVELLER

SMOOTH FINISH FOR WOODEN FLOORS

AVAILABLE SIZE: : 15.9kg



SCAN FOR
DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® WOODEN FLOOR LEVELLER is a latex leveller with excellent adhesion, flexibility and water resistance. It is used prior to the installation of laminate, vinyl and carpet.

CEMIX® WOODEN FLOOR LEVELLER kit contains:

- 1L Primer
- Wooden Floor Leveller (12kg powder & 2.9L liquid)

TYPICAL USES:

CEMIX® WOODEN FLOOR LEVELLER is used to prepare a substrate before the application of flooring materials, including laminate, vinyl and carpet. Suitable for interior use.

ADVANTAGES:

- Easy to mix
- Smooth finish - ideal for the application of vinyl
- Durable finish for use in both commercial and domestic areas

YIELD:

For contents in this kit: Approximately 7m² at a bed thickness of 1mm or 2.3m² at a bed thickness of 3mm.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

Ensure all wooden floor boards are firmly fixed and sanded.

On absorbent surfaces, it is necessary to prime the surface with a brush or roller, using the primer supplied.

MIXING:

1. Add supplied additive to a mixing container. Ensure the additive is mixed by shaking the bottle thoroughly.
2. Add supplied powder to the additive, mixing constantly with a mixing paddle.

APPLICATION:

1. Pour the mixture onto the surface immediately after mixing - it should be in a slurry form.
2. When a screed of uniform bed thickness is required, move it across the surface at a constant speed. Levels may be corrected by applying a greater or lesser amount of the mixture.

DRYING & CURING:

Working time of CEMIX® WOODEN FLOOR LEVELLER is approximately 30 minutes at 20°C.

The surface can be walked on after approximately 3 hours depending on thickness and temperatures.

Allow 24 hours drying time before the installation of carpet and 48 hours before the installation of vinyl.

CLEANING:

Clean tools with alcohol or acetone immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring

WOODEN FLOOR LEVELLER

LIMITATIONS:

Not suitable for exterior use.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

**Read label before use. Keep out of reach of children.
If medical advice is needed, have product container or label at hand.**

DANGER



HAZARD STATEMENTS:

Causes skin irritation. May cause an allergic skin reaction.
Causes serious eye damage. May cause respiratory irritation.
Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

SAFETY INSTRUCTIONS:

Do not breathe dust/fume. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF exposed or concerned:** Call a POISON CENTER/doctor/physician/first aider. **Immediately call a POISON CENTER/doctor/physician/first aider.** **IF ON SKIN:** Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

INGREDIENTS:

Graded sand, CAS: 14808-60-7, 30-60%
Portland cement, CAS: 65997-15-1 1-5%
Calcium aluminate cement, 65997-16-2, 10-30%
Limestone, CAS: 1317-65-3, 10-30%
calcium sulfate, CAS: 7778-18-9, 1-10%
Ingredients determined not to be hazardous, CAS: NA, balance

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring