

RUBBERGUARD 360° WATERPROOFING PIPE SLEEVE

USED AS PART OF THE RUBBERGUARD
WATERPROOFING SYSTEM

AVAILABLE SIZE: : 1pc



SCAN FOR
DETAILS



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® RUBBERGUARD 360° WATERPROOFING PIPE SLEEVE is a non-adhesive tape designed to seal protruding pipework, over cementitious and plasterboard surfaces. It is used as part of the CEMIX® RUBBERGUARD waterproofing system.

TYPICAL USES:

For reinforcing protruding pipework, from 10mm to 50mm in diameter, in conjunction with the CEMIX® RUBBERGUARD system. Suitable for interior use.

ADVANTAGES:

- Seamless seal
- Tear and rupture resistant
- Flexible - elastic recovery when exposed to movement

STANDARDS:

BRANZ appraised when used as part of the the CEMIX® RUBBERGUARD waterproofing system.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with CEMIX® TILE BOND LATEX to stabilise the surface.

After priming, it is recommended to apply a neutral, cure sealant to all wall and floor junctions and joints.

APPLICATION:

1. Identify the width of the pipe and match it to one of the pre-drawn circles on the pipe sleeve.
2. Cut a hole in the CEMIX® RUBBERGUARD 360° WATERPROOFING PIPE SLEEVE to one circle width less than the pipe diameter to ensure a tight fit over the pipe and to produce a funnel shape when embedded onto the wall.
3. Using a spatula, embed the pipe sleeve into this wet coat, ensuring there are no large pockets of membrane nor air behind it.
4. Apply a second coat of CEMIX® RUBBERGUARD waterproofing membrane.

STORAGE & SHELF LIFE:

Store in a cool, dry place.

TECHNICAL DATA:

APPLICATION TEMP.:	5°C - 30°C
--------------------	------------

LIMITATIONS:

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

RUBBERGUARD 360° WATERPROOFING PIPE SLEEVE

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX®PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring