



ROOF & GUTTER REPAIR TAPE

FLEXIBLE RUBBER WATERPROOFING MEMBRANE

.....
AVAILABLE SIZE: 5m



SCAN FOR
 DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® ROOF & GUTTER REPAIR TAPE is a self adhesive tape designed for the flashing and sealing of roofs and gutters.

TYPICAL USES:

CEMIX® ROOF & GUTTER REPAIR TAPE can be used in interior and exterior applications, including:

- Sealing and detailing external sheeting abutments before waterproofing
- Sealing joints between floor and roof sheeting on decks and balconies
- Flashing metal surfaces
- Patching pin holes on roofing and gutter surfaces.

ADVANTAGES:

- Instant sealing

YIELD:

5 linear metres

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

The substrate should be dry.

It is recommended to prime the surface with CEMIX® TILE BOND LATEX to stabilise the surface.

APPLICATION:

1. Unroll and cut CEMIX® ROOF & GUTTER TAPE to the required length, using scissors or a sharp cutter knife.
2. Place the tape over the area to be sealed and while slowly unwinding, remove the release paper and position the tacky side directly over the area to be sealed. It is not recommended to remove the total length of the release paper before adhering the tape into position.
3. Press the tape into position with a spatula, roller or cloth, ensuring air pockets and creases are removed.

Note: Finishes can be applied immediately after the tape is in place. If waterproofing, it is recommended to use CEMIX® ROOF & GUTTER WATERPROOFER directly over the tape surface.

STORAGE & SHELF LIFE:

Store in a cool, dry place.

LIMITATIONS:

Not to be used as an exposed flashing. Cannot be applied to wet or damp surfaces. Cannot be applied to masonry.

If applying over cementitious surfaces, it is recommended to prime the surface with a CEMIX® primer before application.

If applying over metals, ensure that the surface is rust free and if required, treat the rust before application.

Do not apply solvent based finishes directly over the tape surface.



Scan to see
 Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

ROOF & GUTTER REPAIR TAPE

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring