



# POTTERY SEALER

**WATER BASED, PENETRATING & FILM FORMING, CLEAR SEALER**

.....  
**AVAILABLE SIZE: 500ML**



SCAN FOR  
DETAILS



NOTE: Due to updates in progress, packaging may vary.

## DESCRIPTION:

CEMIX® POTTERY SEALER is a water based, penetrating and film forming (hybrid), clear sealer, designed to resist water and stains from paving. When used as a film forming sealer, it produces a matte finish.

## TYPICAL USES:

CEMIX® POTTERY SEALER can be used on a variety of pottery and stone surfaces, including:

- Bird Baths
- Garden Pots and Ornaments
- Carved and Reconstituted Stone

## ADVANTAGES:

- Resists water, stains and dirt
- Ready to use
- Minimises efflorescence
- Inhibits mould growth
- Hybrid sealer: penetrating and film forming

## COVERAGE:

Varies according to the substrate condition and climate. Approximately 5m<sup>2</sup> to 14m<sup>2</sup> per litre of product, per coat.

## PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent sealing and coating.

Ideally, CEMIX® POTTERY SEALER should be applied to new pottery. If applying to existing work, it is recommended to remove any stains, marks, variations etc. from the substrate before application, as the product is likely to magnify these.

Ensure that the substrate is dry before application.

Always carry out a small test area to approve look and feel.

## APPLICATION:

1. Shake before use.
2. Apply the product straight from the spray bottle.

The sealer will dry in approximately 20 minutes at 25°C. Further coats may be required for more porous substrates. If a more satin finish is preferable, build up coats (as required).

## DRYING & CURING TIME:

Drying and curing time may vary depending on the substrate and climate. Drying time is approximately 4 hours. Curing time is up to approximately 48 hours.

## CLEANING:

Clean tools with water immediately after use.

## STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

## LIMITATIONS:

Do not apply if rain is expected within 48 hours.

Not to be used as a waterproofer.

CEMIX® POTTERY SEALER is likely to darken and/or discolour the surface. Carry out a small test area first.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

DECORATIVE SEALERS

Nov 2022 | Page 2

# POTTERY SEALER

Environmental conditions may affect the product's performance over time. Reapplication may be required after two years or more from initial application, depending on these conditions.

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.

**Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.**

**DANGER**



### HAZARD STATEMENT(S):

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

### SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Avoid release to the environment.

### Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash before reuse. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Rinse mouth.

### INGREDIENTS:

Acrylic Polymer, CAS: NA, 30 - 35%  
Polyurethane Hybrid, CAS: NA, 10 - 15%  
Triethoxy (2,4,4-trimethylpentyl)silane, CAS: 35435-21-3, 8 - 10%  
2,4,7,9-tetramethyl-5-decyne-4,7-diol, CAS: 126-86-3, 1 - 1.5%  
Water, CAS: 7732-18-5, 30 - 32%

### DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

### SCAN QR CODE FOR MORE PRODUCT INFORMATION



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
[WWW.CEMIX.CO.NZ](http://WWW.CEMIX.CO.NZ)



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring