



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 1



# PRE-MIXED PASTE ADHESIVE

## READY TO USE INTERIOR WALL & FLOOR TILE ADHESIVE

AVAILABLE SIZE: : 500ml , 1L , 4L , 10L



SCAN FOR DETAILS

### DESCRIPTION:

CEMIX® PRE-MIXED PASTE ADHESIVE is a flexible, water resistant, ready to use, white, tile adhesive, designed for fixing a wide range of tiles onto a variety of substrates

### TYPICAL USES:

CEMIX® PRE-MIXED PASTE ADHESIVE can be used on concrete, cement renders, screeds, fibrous cement sheeting, plasterboard and CEMIX® approved waterproofing membranes. Suitable for use in interior wall and floor applications, including bathrooms, toilets, laundries and kitchens. Do not use in submersed areas, like showers and baths.

### ADVANTAGES:

Ready and easy to use.

### YIELD:

Approximately 2m<sup>2</sup> per litre of product.

### STANDARDS:

All workmanship must be carried out in accordance with AS3958.1.

### PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations. All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

CEMIX® screeds, floor levellers, plasters and approved waterproofing membranes must be allowed to cure.

It is recommended to prime the surface with a CEMIX® TILE BOND LATEX before the application of CEMIX® PRE-MIXED PASTE ADHESIVE.

CEMIX® PRE-MIXED PASTE ADHESIVE is also suitable for tiling over timber floors, provided that a fibre cement sheet tile underlay is initially installed over the timber floor.

### MIXING:

No mixing required.

### APPLICATION:

1. Stir before use.
2. Spread the mixture evenly over the surface with a suitably sized notched trowel.
3. Install the tiles with pressure, twisting to ensure good adhesion between the substrate and tile.

**Note:** A minimum final bed thickness between 3mm to 10mm is recommended for walls, and 6mm to 10mm for floors. Do not spread more than 1m<sup>2</sup> of adhesive at any one time as skinning may occur, affecting final adhesion. Ensure that the tiles are fully supported with the adhesive when being laid.

### DRYING & CURING:

Once the tiles have been laid, they must not be trafficked upon or disturbed for a minimum of 24 hours at 20°C. If application is over a CEMIX® approved waterproofing membrane or a non-porous substrate, allow for a minimum of 48 hours at 20°C. Note that the cure time will be delayed if the temperature is below 20°C, if there is insufficient air circulation or if application is over a CEMIX® approved waterproofing membrane.

### CLEANING:

Clean tools with water immediately after use.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars

Repairs & Grouts

Admixtures

Decorative Sealers

Waterproofing

Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

## PRE-MIXED PASTE ADHESIVE

### STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

### LIMITATIONS:

Not suitable for tiling directly over flexible substrate i.e. timber, plywood, particleboard, MDF and Masonite etc. Not suitable for use with porcelain tiles. Not suitable for continuous water immersion applications i.e. swimming pools and spas etc.

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.

**Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.**

**DANGER**



### HAZARD STATEMENTS:

Causes serious eye damage. Causes skin irritation.

### SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/face protection.

### RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/physician/first aider. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

### INGREDIENTS:

Portland cement, CAS: 65997-15-1, 30-60%

limestone, CAS: 1317-65-3, 40-80%

acrylic copolymer, proprietary, CAS: NA, 20-50%

water, CAS: 7732-18-5, 10-20%

Ingredients determined not to be hazardous CAS: NA, <10%

### DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

### SCAN QR CODE FOR MORE PRODUCT DETAILS:



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061

AUCKLAND NEW ZEALAND

0800 ASK CEMIX | +64 09 636 1000

[WWW.CEMIX.CO.NZ](http://WWW.CEMIX.CO.NZ)



Twitter/CemixNZ



Facebook/CemixNZ



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars

Repairs & Grouts

Admixtures

Decorative Sealers

Waterproofing

Tiling & Flooring