



SUPER PRIMER

WATER BASED PRIMER FOR NON-POROUS SURFACES

.....
AVAILABLE SIZES: 1L | 4L



SCAN FOR
DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® SUPER PRIMER is a water based primer, designed to improve the adhesion of CEMIX® products to a variety of smooth, dense and non-porous substrates.

TYPICAL USES:

CEMIX® SUPER PRIMER can be used on concrete, masonry, cement renders, screeds, fibrous cement sheeting, plasterboard, timber, timber sheeting (plywood and particleboard), PVC, plastic, stone and ceramic tiles. It can be used with the subsequent application of CEMIX® tile adhesives, floor levellers and floor repairers on substrates as per the manufacturer's recommendations for these. Suitable for interior and exterior use.

ADVANTAGES

- Suitable for tile on tile application
- Can be used on PVC and plastic

COVERAGE:

Varies according to the substrate condition. Approximately 6m² to 10m² per litre of product.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

Dampen the substrate with clean water immediately before the application of CEMIX® SUPER PRIMER.

MIXING:

Use CEMIX® SUPER PRIMER undiluted. No mixing required.

APPLICATION:

1. Stir before use.
2. Apply the undiluted product to the substrate with a brush or roller.

Note: Allow CEMIX® SUPER PRIMER to dry before the subsequent application of another CEMIX® product.

DRYING & CURING TIME:

Drying time depends on the substrate, substrate condition, climate, the type of application and the materials being applied. As a guideline, drying time is approximately 20 minutes.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity. Do not expose to direct sunlight in storage.

LIMITATIONS:

Ceramic tile substrates must be de-glazed before application.

Not suitable for continuous water immersion applications i.e. swimming pools and spas etc.

If your project requires Building Consent, please email



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

ADMIXTURES

August 2022 | Page Number 2

SUPER PRIMER

info@cemix.co.nz about the suitability of this product before use.

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.

Not regulated for transport of Dangerous Goods.

INGREDIENTS:

Vinyl acrylic copolymer, CAS: Not Available, 30-50%
Styrene/ butadiene copolymer, CAS: Not Available, 10-30%
Inorganic mineral filler, CAS: Not Available, 10-30%
Other non hazardous ingredients, CAS: Not Available, 1-10%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring