



# A. P. R. A.

## ALL PURPOSE FORMWORK RELEASE AGENT

.....

**AVAILABLE SIZES: 4L**



SCAN FOR  
DETAILS

**NOTE: Due to updates in progress, packaging may vary.**

**DESCRIPTION:**

CEMIX® A.P.R.A. is an amber coloured, formwork release agent, designed to break the bond between cast concrete and its formwork, allowing for an easy release.

**TYPICAL USES:**

CEMIX® A.P.R.A. may be used on most formwork for concrete casting.

**ADVANTAGES:**

- Can be safely used on placing tools

**COVERAGE:**

Type of formwork coverage per litre of product:

- Steel: 30m<sup>2</sup> to 60m<sup>2</sup>
- Smooth Plywood: 20m<sup>2</sup> to 40m<sup>2</sup>
- Rough Sawn Timber: 15m<sup>2</sup> to 25m<sup>2</sup>

**PREPARATION:**

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

The substrate must be dry.

**MIXING:**

Ready to use. No mixing required.

**APPLICATION:**

1. Shake / stir before use.
2. Apply a thin coat of product by brush or spayer onto the casting face, back and sides, before each pour or cast of concrete.

Pouring can take place immediately after product application or within 24 hours.

**CLEANING:**

Clean tools with water immediately after use.

**STORAGE & SHELF LIFE:**

Up to 12 months when stored in the original, unopened packaging.

**LIMITATIONS:**

May stain concrete cast work.

Avoid application of thick coating to new hardboard or plywood formwork, as this may damage the surface finish. Avoid contact with reinforcements, as the product prevents concrete from binding to steel.

The product creates a dust film when it comes into contact with concrete.

Brush film away before any subsequent work is carried out.

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.

**TECHNICAL DATA:**

APPEARANCE	Yellow
APPLICATION TEMPERATURE	30°C - 300°C
<i>The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.</i>	



Scan to see  
Cemix videos

**Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)**

Concrete & Mortars    Repairs & Grouts    Admixtures    Decorative Sealers    Waterproofing    Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

ADMIXTURES

April 2026 | Page 2

# A.P.R.A

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

## DANGER



### HAZARD STATEMENTS:

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

### PREVENTION:

Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection and face protection. [In case of inadequate ventilation] wear respiratory protection. Avoid release to the environment. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

### RESPONSE:

IF SWALLOWED: Immediately call a POISON CENTER (0800 764 766)/doctor/physician/first aider. Do NOT induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON CENTER (0800 764 766)/doctor/physician/first aider. IF ON SKIN: Wash with plenty of water and soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.

### INGREDIENTS:

Diesel, CAS: 68334-30-5, 80-90%  
4'-aminoacetanilide, CAS: 122-80-5, 4-5%  
Mineral oil, CAS: Not avail., 4-5%

### DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

### SCAN QR CODE FOR MORE PRODUCT INFORMATION



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring