



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 1

CEMIX RUBBERGUARD PEEL & SEAL TAPE

USED AS PART OF THE RUBBERGUARD WATERPROOFING SYSTEM

AVAILABLE SIZE: 5m



SCAN FOR DETAILS



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® RUBBERGUARD PEEL & SEAL TAPE is a self adhesive tape designed to reinforce straight and right angled joints, over cementitious and plasterboard surfaces. It is used as part of the CEMIX® RUBBERGUARD waterproofing system.

TYPICAL USES:

For reinforcing straight and right angled joints in conjunction with the CEMIX® RUBBERGUARD system. Suitable for interior use.

ADVANTAGES:

- Instant sealing

YIELD:

5 linear metres

STANDARDS:

BRANZ appraised when used as part of the the CEMIX® RUBBERGUARD waterproofing system.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with CEMIX® TILE BOND LATEX to stabilise the surface.

After priming, it is recommended to apply a neutral, cure sealant to all wall and floor junctions and joints.

APPLICATION:

1. Unroll and cut CEMIX® RUBBERGUARD PEEL & SEAL TAPE to the required length, using scissors or a sharp cutter knife.
2. Place the tape over the area to be sealed and while slowly unwinding, remove the release paper and position the tacky side directly over the area to be sealed. It is not recommended to remove the total length of the release paper before adhering the tape into position.
3. Press the tape into position with a spatula, roller or cloth, ensuring air pockets and creases are removed.

Note: Finishes can be applied immediately after the tape is in place. If waterproofing, it is recommended to use CEMIX® RUBBERGUARD directly over the tape surface.

STORAGE & SHELF LIFE:

Store in a cool, dry place.

TECHNICAL DATA:

APPLICATION TEMP.:	5°C - 30°C
--------------------	------------

LIMITATIONS:

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.



Scan to see CEMIX videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

CEMIX RUBBERGUARD PEEL & SEAL TAPE

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX®PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring