



RUBBERGUARD REINFORCING FABRIC TAPE

USED AS PART OF THE RUBBERGUARD
WATERPROOFING SYSTEM

AVAILABLE SIZE: 5m



SCAN FOR
DETAILS

DESCRIPTION:

CEMIX® RUBBERGUARD FABRIC TAPE is a non-adhesive tape designed to reinforce less uniformed joints, over cementitious and plasterboard surfaces. It is used as part of the CEMIX® RUBBERGUARD waterproofing system..

TYPICAL USES:

For reinforcing less uniformed joints in conjunction with the CEMIX® RUBBERGUARD system. Suitable for interior use.

ADVANTAGES:

- Flexible - can be placed around less uniformed joints

YIELD:

10 linear metres

STANDARDS:

BRANZ appraised when used as part of the the CEMIX® RUBBERGUARD waterproofing system.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

It is recommended to prime the surface with CEMIX® TILE BOND LATEX to stabilise the surface.

After priming, it is recommended to apply a neutral, cure sealant to all wall and floor junctions and joints.

APPLICATION:

1. Unroll and cut CEMIX® RUBBERGUARD REINFORCING FABRIC TAPE to the required length, using scissors or a sharp cutter knife.
2. Measure the tape to the length of the area to be sealed, then dry cut the tape.
3. Apply the tape to a wetcoat of CEMIX® RUBBERGUARD waterproofing membrane.
4. Using a brush, embed the fabric tape into this wet coat, ensuring there are no large pockets of membrane nor air behind it.
5. Apply a second coat of CEMIX® RUBBERGUARD waterproofing membrane.

Note: The fabric tape must be embedded into a wet coat of a CEMIX® RUBBERGUARD. When applied correctly, excess waterproofing membrane will seep through the face of the fabric tape.

STORAGE & SHELF LIFE:

Store in a cool, dry place.

TECHNICAL DATA:

APPEARANCE:	Reinforcing polymer fabric tape
APPLICATION TEMP.:	5°C - 30°C

LIMITATIONS:

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

Dec 2022 | Page 2

RUBBERGUARD REINFORCING FABRIC TAPE

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX®PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring