




PAVING SEALER

WATER BASED, PENETRATING & FILM FORMING, CLEAR SEALER

AVAILABLE SIZE: 1L & 4L



SCAN FOR
DETAILS



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® PAVING SEALER is a water based, penetrating and film forming (hybrid), clear sealer, designed to resist water and stains from paving. When used as a film forming sealer, it produces a matte finish.

TYPICAL USES:

CEMIX® PAVING SEALER is ideal for use on pavers. Suitable for use in interior and exterior applications.

ADVANTAGES:

- Ready to use
- Resists water, stains and dirt.
- Minimises efflorescence
- Inhibits mould growth
- UV resistant
- Hybrid sealer: penetrating and film forming

COVERAGE:

Varies according to the substrate condition and climate. Approximately 5m² to 14m² per litre of product, per coat.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent sealing and coating.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

Ideally, CEMIX® PAVING SEALER should be applied to new, freshly laid pavers. If applying to existing work, it is recom-

mended to remove any stains, marks, variations etc. from the substrate before application, as the product is likely to magnify these.

Ensure that the substrate is dry before application.

Always carry out a small test area to approve look and feel.

APPLICATION:

1. Stir before use.
2. Apply the product generously with a brush, roller or sprayer.
3. Repeat for a second coat.

Ensure a coverage of at least 5m² per litre, per coat. Further coats may be required for more porous substrates. Allow for a minimum of 4 to 6 hours between coats in a warmer climate, and up to 24 hours in cooler climate. If a more satin finish is preferable, build up coats (as required).

Note: Never apply more product than is being absorbed. If the product pools, brush the excess off. Ensure that there is no rising damp as this will make the sealed surface cloudy in appearance. Over application can make the surface slippery, especially when wet.

DRYING & CURING TIME:

Drying and curing time may vary depending on the substrate and climate. Drying time is approximately 4 hours. Curing time is up to approximately 48 hours.

CLEANING:

Clean tools with water immediately after use.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

PAVING SEALER

STORAGE & SHELF LIFE:

Up to 24 months when stored in the original, unopened packaging.

DISPOSAL:

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

LIMITATIONS:

Do not apply if rain is expected within 48 hours.

Not to be used as a waterproofer.

CEMIX® PAVING SEALER is likely to darken and/or discolour the surface. Carry out a small test area first.

Environmental conditions may affect the product's performance over time. Reapplication may be required after two years or more from initial application, depending on these conditions.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

PREVENTION:

Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wash all exposed external body areas thoroughly after handling.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/physician/first aider. **IF SWALLOWED:** Call a POISON CENTER/doctor/physician/first aider if you feel unwell. **IF ON SKIN:** Wash with plenty of water. Rinse mouth. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

INGREDIENTS:

Acrylic Polymer, CAS: NA, 30 - 35%, Polyurethane Hybrid, CAS: NA, 10 - 15%, Triethoxy (2,4,4-trimethylpentyl)silane, CAS: 35435-21-3, 8 - 10%, 2,4,7,9-tetramethyl-5-decyne-4,7-diol, CAS: 126-86-3, 1 - 1.5%, Water, CAS: 7732-18-5, 30 - 32%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR FURTHER INFORMATION ON THE PRODUCT



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring