

Nov 2022 | Page 1



# **BITUPATCH**

## PERMANENT ASHPHALT REPAIR **FOR POTHOLES**

**AVAILABLE SIZE: 20kg** 



NOTE: Due to updates in progress, packaging may vary.

#### **DESCRIPTION:**

CEMIX® BITUPATCH is a ready to use, cold mix bitumen asphalt, designed for repairing potholes in asphalt roads, driveways and paths. It is simply and easily placed directly from the bag in to the hole.

#### **TYPICAL USES:**

- Potholes
- Speed bumps
- Ramps

#### **ADVANTAGES:**

· Ready to use

#### YIELD:

Approximate yield for 20kg bag: 0.01m3

#### PREPARATION:

Thoroughly clean the area to be filled or reinstated. It should be free of any loose and deleterious materials.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

For pothole repair, where possible, it is recommended to create a vertical edge to the hole for CEMIX® BITUPATCH to butt up against.

#### **APPLICATION:**

1. Place CEMIX® BITUPATCH on the area to be repaired. When repairing potholes, ensure the middle of the placed product is higher than the sides, by 5mm to 10mm depending on the repair area size. This will counteract subsidence caused by compacting.

2. Compact the hole. For best results, use a compacting plate or steel wheel roller. For smaller areas, use a large flat material, such as a timber post, compressed with a rubber mallet or similar.

CEMIX® BITUPATCH can be applied between 5°C to 30°C. However, for best results, use between 21°C to 30°C.

#### **DRYING & CURING:**

Drying time depends on the climate.

#### **CLEANING:**

Clean tools with a solvent thinner after use.

#### **STORAGE & SHELF LIFE:**


Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

#### LIMITATIONS:

Product is not suitable for feathering i.e. forming thin edges.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.



#### **REPAIR & GROUTS**

Nov 2022 | Page 2

### **BITUPATCH**







#### **HAZARD STATEMENTS:**

May cause cancer. Causes damage to organs. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure.

#### **SAFETY INSTRUCTIONS:**

Obtain special instructions before use. Do not breathe mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product.

#### **RESPONSE:**

IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider. Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

#### **INGREDIENTS:**

Graded sand, CAS: 14808-60-7, >60% Bitumen road making, CAS: 8052-42-4, <10%

Proprietary polymer, CAS: NA, <3%

#### **DISCLAIMER:**

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

#### SCAN QR CODE FOR MORE PRODUCT INFORMATION





19 ALFRED STREET ONEHUNGA 1061 AUCKLAND NEW ZEALAND 0800 ASK CEMIX | +64 09 636 1000 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos

