

ADMIXTURES

September 2022 | Page Number 1



C.F.R.A. CONCRETE FORMWARE RELEASE AGENT

AVAILABLE SIZES: 4L | 20L



NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX[®] C.F.R.A. is a formwork release agent, designed to break the bond between cast concrete and its formwork, allowing for an easy release.

TYPICAL USES:

 $\mathsf{CEMIX}^{\texttt{®}}$ C.F.R.A. may be used on most formwork for concrete casting.

ADVANTAGES:

- Can be safely used on placing tools
- Produces a stain-free concrete finish

COVERAGE:

Covers up to 18m² per litre of product when used with suitable equipment.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

The substrate must be dry.

MIXING:

Ready to use. No mixing required.

APPLICATION:

- 1. Shake/stir before use.
- 2. Apply a thin coat of product by brush or spayer onto the casting face, back and sides, before each pour or cast of concrete.

Pouring can take place immediately after product application or within 24 hours.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

Avoid application of thick coating to new hardboard or plywood formwork, as this may damage the surface finish. Avoid contact with reinforcements, as the product prevents concrete from binding to steel.

The product creates a dust film when it comes into contact with concrete. Brush film away before any subsequent work is carried out.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER

HAZARD STATEMENTS:

- Causes skin irritation
- May cause allergy or asthma symptoms or breathing difficulties if inhaled



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring

0800 ASK CEMIX

ADMIXTURES



MORE THAN CONCRETE

September 2022 | Page Number 2

C.F.R.A.

- May cause an allergic skin reaction
- Suspected of causing cancer
- May cause drowsiness or dizziness
- · May be fatal if swallowed and enters airways
- Toxic to aquatic life with long lasting effects

SAFETY INSTRUCTIONS:

Obtain special instructions before use. Avoid breathing mist/ vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace.

INGREDIENTS:

Mineral Oil, CAS: NA, 72-75% Diesel, CAS: 68334-30-5, 20-25% 4'-aminoacetanilide, CAS: 122-80-5, 4-5%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN OR CODE FOR MORE PRODUCT INFORMATION





