



ACRYLBOND

WATER BASED BONDING AGENT FOR POROUS CEMENTITIOUS SURFACES (INDOOR USE)

.....
AVAILABLE SIZES: 1L | 5L | 20L



SCAN FOR
DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® ACRYLBOND is a water based bonding agent, designed to improve the adhesion of CEMIX® products to porous, cementitious substrates, while providing waterproofing properties.

TYPICAL USES:

CEMIX® ACRYLBOND can be used on concrete, masonry, cement renders, screeds, fibrous cement sheeting, plasterboard, timber, timber sheeting (plywood and particleboard) and stone. It can be used with the subsequent application of CEMIX® tile adhesives, floor levellers and floor repairers on substrates as per the manufacturer's recommendations for these. Suitable for interior and exterior use.

ADVANTAGES:

- Can be used as a primer and admixture
- Provides waterproofing properties

COVERAGE:

Varies according to the substrate condition. Approximately 6m² per litre of product.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

Smooth surfaces on new and old concrete should be scabbled. All substrates should be structurally sound, securely fastened

and properly supported to eliminate any movement that may cause cracking.

Dampen the substrate with clean water immediately before the application of CEMIX® ACRYLBOND.

MIXING:

As a Primer:

Use CEMIX® ACRYLBOND undiluted. No mixing required.

As an Additive:

Refer to the manufacturer's recommendations for the CEMIX® product being used.

APPLICATION:

As a Primer:

1. Stir before use.
2. Apply the undiluted product to the substrate with a brush, roller or sprayer.

Note: Ensure CEMIX® ACRYLBOND is tacky before the subsequent application of the CEMIX® product.

As an Additive:

Refer to the manufacturer's recommendations for the CEMIX® product being used.

DRYING & CURING TIME:

As a Primer:

Drying time depends on the substrate, substrate condition, climate, the type of application and the materials being applied. As a guideline, drying time is approximately 20 minutes.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

ADMIXTURES

August 2022 | Page Number 2

ACRYLBOND

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

Not suitable for application on non-porous substrates.

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:

Harmful if swallowed. Causes skin irritation. Causes serious eye damage.

PREVENTION:

Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call THE NATIONAL POISON CENTRE (0800 764 766) or a doctor/physician. Take off contaminated clothing and wash before reuse. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. **IF INHALED:** Remove victim to fresh air and keep at rest in a position. Comfortable for breathing.

INGREDIENTS:

Styrene acrylic copolymer proprietary, CAS: NA, 75 - 80%
Water, CAS: 7732-18-5, 20 - 25%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring