

EZY LEVEL

SELF LEVELLING COMPOUND

AVAILABLE SIZE: 8KG & 18 KG

SCAN FOR DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:
CEMIX® EZY LEVEL is a premium self-levelling floor compound designed to smooth and level concrete floors and screeds from 2–30mm in one easy step. Ideal for preparing floors before applying tiles, vinyl, timber, or other coverings.

TYPICAL USES:
Use CEMIX® EZY LEVEL to prepare a smooth, even surface before laying any type of floor covering. Perfect for:
- Levelling uneven or rough concrete floors before tiling or vinyl installation.
- Preparing floors for carpet or timber flooring in renovation projects.
- Creating a level base over existing screeds before applying decorative coatings.
- Smoothing floors with underfloor heating prior to installing the final floor finish.

ADVANTAGES:
- Fast-setting performance – walkable after 4–6 hours, ready for coverings within 24–48 hours.
- Smooth self-levelling finish – creates an even base with minimal effort.
- Versatile thickness – suitable for applications from 2–30mm.
- Underfloor heating compatible – ideal for modern renovation and comfort flooring systems.

COVERAGE:
- 1.7kg/m^2
- Coverage may vary depending on surface texture, porosity and bed thickness.

PREPARATION:
Ensure the surface is clean, sound, and free from dust, grease, oil, paint, wax, or any loose or friable material that could affect adhesion. Remove all contaminants such as curing compounds or sealers before beginning project. The surface prior to application should be primed using a Cemix primer to ensure a strong bond to the substrate.

SUBSTRATE TEST:
Check that the surface is absorbent. Sprinkle a small amount of water onto the concrete — if it soaks in readily, the surface is suitable. If the water beads or sits on top, any coatings or sealers must be removed before use. When in doubt, always perform a test patch.

MIXING:
Water ratio: 216-224ml per kg of product.

Start with the lower end of the ratio — more water can be added if needed to reach the correct flow. Do not over water.

Floor leveller hardens quickly therefore it is essential to mix thoroughly in the shortest amount of time.

1. Pour clean water into a mixing container (start with approx. 216ml per kg of product).
2. Gradually add CEMIX® EZY LEVEL to the water while mixing with a drill and paddle until a smooth, lump-free consistency is achieved.
3. Adjust with a little extra water if required to achieve a smooth consistency.

Note: Only mix as much material as can be applied within 15–20 minutes. For layers under 5mm, use a trowel to help spread and level the product.

APPLICATION:
Pour the mixed CEMIX® EZY LEVEL onto the prepared surface and spread evenly using a gauge rake or trowel to achieve the desired thickness (2–30mm). Allow the product to self-level and settle — minimal trowelling is required.

For areas requiring greater depth:
Bulk Fill: Apply in layers up to 50mm total thickness.
1. Allow the first layer to set (typically 3–4 hours) before applying the second.
2. Prime the first layer lightly with Cemix® Primer before re-applying to ensure a strong bond between layers.

Do not attempt to rework the surface once setting has begun.

FINISHING:
Roll with a spiked roller in two directions to release any trapped air. For best results, apply during cooling or falling temperatures.

EZY LEVEL

DRYING & CURING TIME:
Can be walked on after 4–6 hours. Ready for tiles in 24 hours and other floor coverings in 48 hours. Drying time will vary with temperature and humidity. Make sure there's good air flow to help the leveller cure properly. Wait at least 48 hours before applying Cemix waterproofing membranes.

CLEANING:
Clean tools and equipment immediately with water before material sets.

STORAGE & SHELF LIFE:
Up to 12 months when stored in the original, unopened packaging, in a dry place. Store in a well-ventilated place.

DISPOSAL:
Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

LIMITATIONS:
Check Technical datasheet for the comprehensive list of limitations for this product available at www.cemix.co.nz

- CEMIX® EZY LEVEL is not designed as a finished wear surface and should not be used on driveways or areas exposed to vehicle traffic.
- For internal wet areas, apply a suitable Cemix® liquid waterproofing membrane over the leveled surface to ensure complete waterproof protection.
- Do not mix with other cements or products.
- Protect the fresh floor from water, damp, and condensation for at least 24 hours.
- Stick to the recommended water amount and thickness. Don't add water once it starts to set.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Suspected of causing genetic defects. Causes damage to organs through prolonged or repeated exposure.

SAFETY INSTRUCTIONS:
Do not breathe dust/fume. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood.

Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

RESPONSE:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a POISON CENTER (0800 764 766)/ doctor/physician/first aider if you feel unwell. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: remove person to fresh air and keep comfortable for breathing.

INGREDIENTS:
silica crystalline - quartz, CAS: 14808-60-7, 25-50%. Calcium carbonate, CAS:471-34-1, 10-50%. Portland cement, CAS: 65997-15-1, 10-25%. Ingredients determined not to be hazardous, CAS: NA, <10%.

DISCLAIMER:
Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

PLEASE REFER TO THE DATASHEET AT WWW.CEMIX.CO.NZ FOR FURTHER INFORMATION AND INSTRUCTIONS.

SCAN QR CODE FOR MORE PRODUCT INFORMATION

CEMIX® PRODUCTS LTD
19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ

Twitter/CemixNZ
Facebook/CemixNz
Pintrest/CemixNZ
YouTube/CemixVideos

Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars | Repairs & Grouts | Admixtures | Decorative Sealers | Waterproofing | Tiling & Flooring