



# FAST SET TILE ADHESIVE

## RAPID SETTING MULTIPURPOSE TILE ADHESIVE

AVAILABLE SIZE: : 5kg, 10kg



SCAN FOR  
DETAILS



WATER  
RESISTANT



CURING  
TIME

NOTE: Due to updates in progress, packaging may vary.

### DESCRIPTION:

CEMIX® FAST SET TILE ADHESIVE is a flexible, polymer modified, water resistant, grey cement based tile adhesive, designed specifically for fixing non-porous tiles onto a variety of substrates. It has a rapid setting time of 2 hours.

### TYPICAL USES:

CEMIX® FAST SET TILE ADHESIVE can be used on concrete, cement renders, screeds, fibrous cement sheeting, plaster-board and CEMIX® approved waterproofing membranes. Suitable for use in interior and exterior wall and floor applications, including bathrooms, toilets, laundries, kitchens, decks and verandahs.

### ADVANTAGES:

- Fast setting time – can apply grout after 2 hours
- Ideal for fixing non-porous tiles, including granite and porcelain

### YIELD:

Varies according to the substrate condition and trowel size.

Approximates per kg of product using a notched trowel sized:

6mm trowel: 0.4m<sup>2</sup>

10mm trowel: 0.25m<sup>2</sup>

### STANDARDS:

All workmanship must be carried out in accordance with AS3958.1.

### PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

CEMIX® screeds, floor levellers, plasters and approved waterproofing membranes must be allowed to cure.

It is recommended to prime the surface with a CEMIX® TILE BOND LATEX before the application of CEMIX® FAST SET TILE ADHESIVE.

CEMIX® FAST SET TILE ADHESIVE. is also suitable for tiling over timber floors, provided that a fibre cement sheet tile underlay is initially installed over the timber floor.

### MIXING:

1. Add clean water to a mixing container. Use approximately 240ml of water per kg of product.
2. Add CEMIX® FAST SET TILE ADHESIVE slowly to the water, mixing constantly with a mixing paddle, until a creamy consistency is achieved.

**Note:** Only mix as much product as can be used within 5 minutes. Do not aerate the mixture by stirring over vigorously or for too long. The mix should be stiff enough to keep its shape when spread with a notched trowel.

### APPLICATION:

1. Spread the mixture evenly over the surface with a suitably sized notched trowel.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

# FAST SET TILE ADHESIVE

2. Install the tiles with pressure, twisting to ensure good adhesion between the substrate and tile.

In more demanding situations, it is preferable to also spread the back of the tiles with a thin layer of mixture.

**Note:** A minimum final bed thickness between 6mm to 10mm is recommended for floors. Do not spread more than 1m<sup>2</sup> of adhesive at any one time as skinning may occur, affecting final adhesion. Ensure that the tiles are fully supported with the adhesive when being laid.

### DRYING & CURING:

Once the tiles have been laid, they must not be trafficked upon or disturbed for a minimum of 24 hours at 20°C. If application is over a CEMIX® approved waterproofing membrane or a non-porous substrate, allow for a minimum of 48 hours at 20°C. Note that the cure time will be delayed if the temperature is below 20°C, if there is insufficient air circulation or if application is over a CEMIX® approved waterproofing membrane.

### CLEANING:

Clean tools with water immediately after use. If material becomes set on tools, remove using CEMIX® CONCRETE DISSOLVER.

### STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

### LIMITATIONS:

Not suitable for tiling directly over flexible substrate i.e. timber, plywood, particleboard, MDF and Masonite etc. Not suitable for use with porcelain tiles. Not suitable for continuous water immersion applications i.e. swimming pools and spas etc.

If your project requires Building Consent, please email [info@cemix.co.nz](mailto:info@cemix.co.nz) about the suitability of this product before use.

**Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.**

**DANGER**



### HAZARD STATEMENTS:

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

### SAFETY INSTRUCTIONS:

Obtain special instructions before use. Do not breathe dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace.

### RESPONSE:

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF exposed or concerned:** Call a POISON CENTER/doctor/physician/first aider. **Immediately call a POISON CENTER/doctor/physician/first aider.** Specific treatment (see advice on this label). **IF ON SKIN:** Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

### INGREDIENTS:

Portland cement, CAS: 65997-15-1, 30-60%  
Silica crystalline - quartz, CAS: 14808-60-7, 30-60%  
silica, fumes, CAS: 69012-64-2, 1-10%  
Ingredients determined not to be hazardous, CAS: NA, balance

### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
[WWW.CEMIX.CO.NZ](http://WWW.CEMIX.CO.NZ)



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

## FAST SET TILE ADHESIVE

### DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX®PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

### SCAN QR CODE FOR MORE PRODUCT DETAILS:



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring