



TILE BOND LATEX PRIMER & ADDITIVE

.....
AVAILABLE SIZE: 1L, 4L, 20L



SCAN FOR
DETAILS

NOTE: Due to updates in progress, packaging may vary.

DESCRIPTION:

CEMIX® TILE BOND LATEX is a modified latex, designed to prime porous substrates. It can also be used as an additive, in place of water, for CEMIX® powder tile adhesives and grout. It improves adhesion, workability, and is resistant to water and frost.

TYPICAL USES:

CEMIX® TILE BOND LATEX can be used on concrete, cement renders, screeds, fibrous cement sheeting, plasterboard and CEMIX® approved waterproofing membranes. When used as a primer, suitable for use in interior wall and floor applications, including bathrooms, toilets, laundries and kitchens. When used as an additive, suitable for interior and exterior use.

ADVANTAGES:

- Stabilises the surface, making it ideal for the application of adhesives
- When added to grout, improves adhesion, workability and water resistance

YIELD:

As a Primer:

Varies according to the substrate condition. Approximately 5m² to 8m² per litre of product.

As an Additive:

Refer to manufacturer's recommendations for CEMIX® powder tile adhesive or grout.

STANDARDS:

All workmanship must be carried out in accordance with AS3958.1.

PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive bonding.

New concrete should be left with a wood float finish and sufficiently aged as per manufacturer's recommendations.

Smooth surfaces on new and old concrete should be scabbled.

All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement that may cause cracking.

SUBSTRATE TEST:

The concrete substrate must be absorbent or porous. Test this by sprinkling water on the surface. If the water readily soaks into the concrete, the surface is suitable for application. If the water beads on the surface, the concrete is not suitable for application and any previous coatings need to be removed.

MIXING:

As a Primer:

Use CEMIX® TILE BOND LATEX undiluted. No mixing required.

As an Additive:

Refer to manufacturer's recommendations for CEMIX® powder tile adhesive or grout.

APPLICATION:

As a Primer:

1. Stir before use.
2. Apply the undiluted product to the substrate with a brush or roller.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

TILE BOND LATEX

3. Two coats may be required on particularly porous substrates. Ensure that the surface is tacky before re-application.

As an Additive:

Use as a total water replacement for CEMIX® powder tile adhesive or grout.

DRYING & CURING:

As a Primer:

Drying time depends on the substrate, substrate condition, climate, the type of application and the materials being applied. As a guideline, a CEMIX® adhesive can be applied after approximately 20 minutes.

As an Additive:

Refer to manufacturer’s recommendations for CEMIX® powdered tile adhesive or grout.

CLEANING:

Clean tools with water immediately after use.

STORAGE & SHELF LIFE:

Up to 12 months when stored in the original, unopened packaging, in a dry place at 23°C and 50% relative humidity.

LIMITATIONS:

If your project requires Building Consent, please email info@cemix.co.nz about the suitability of this product before use.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:

Harmful if swallowed. Causes skin irritation. Causes serious eye damage.

SAFETY INSTRUCTIONS:

Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/physician/first aider. Specific treatment (see advice on this label). IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. IF ON SKIN: Wash with plenty of water. Rinse mouth.

INGREDIENTS:

caboxylated styrene butadiene copolymer, CAS: NA, 25-30% water, CAS: 7732-18-5, 70-75%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product’s packaging, CEMIX® PRODUCTS LTD does not give any warranty expressed or implied as to suitability for any particular use. For all advice concerning the use or suitability of this product for a particular application, please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD, who will refund or replace it at no cost, in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT DETAILS:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix’s wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring