



MORE THAN CONCRETE



SUPER PRIMER

WATER BASED, SOLVENT FREE PRIMER FOR SMOOTH, DENSE AND NON-POROUS SURFACES

AVAILABLE SIZES: 1kg | 4kg



READY TO USE



DRYING TIME



NON TOXIC



SCAN FOR DETAILS

DESCRIPTION

CEMIX® SUPER PRIMER is a water-based primer used for improving the adhesion of CEMIX products to smooth, dense and various non porous substrates. It is easy to apply with a brush or roller with applications of subsequent products able to take place with minimal downtime. Specially formulated, ready to use primer, that enhances bond to non-porous surfaces or substrates. CEMIX SUPER PRIMER is suitable for internal and external wall or floor applications.

FOR USE WITH

Cemix Super Primer is compatible with subsequent applications of CEMIX manufactured tile adhesives, floor levelling compounds and in non fully immersed conditions with CEMIX manufactured undertile waterproofing membranes. For use on to smooth, dense and non-porous surfaces.

TYPICAL SUBSTRATES FOR TILE ADHESIVES

Internal particleboard, plywood, sheet timber, medium density fibre-cement sheet, compressed fibre-cement sheet, jointing compound over plasterboard, James Hardie Scyon, concrete, renders, screeds, masonry and lightweight concrete blocks, autoclaved aerated concrete (AAC), *existing glazed tiles (not suitable for shower floors or permanently immersed conditions).

TYPICAL SUBSTRATES FOR FLOOR LEVELLERS

Internal particleboard, plywood, sheet timber for Cemix Wooden Floor Leveller only, compressed fibre-cement sheet, concrete, masonry and lightweight concrete blocks, autoclave aerated concrete (AAC), *existing glazed tiles (tiles to be de-glazed before priming). Note: Not suitable for steel trowelled finish concrete where floor leveller is being applied. For further information contact Cemix Technical Support.

SUBSTRATE PREPARATION

The surface to be primed must be clean, firm and free of dust, dirt, oil, grease, curing compounds, release agents and degraded and unsuitable old surface coatings. Ensure surfaces are dry prior to application, with no residue or permanent dampness. Surfaces must be suitable for the application of the subsequent product being used.

APPLICATION

Stir product before use. Spread the material using a brush or long nap roller to cover at a rate of 6 - 10m² per litre over the entire surface to be primed. For floor levelling toppings application and highly absorbent substrates dilute with water 1:1 by volume. All tools should be cleaned with water immediately after use.

ADVANTAGES

- Improves adhesion
- Non Toxic
- Excellent Bond
- Suitable for tile on tile application
- Provides excellent adhesion to PVC and plastics
- Ready for use. Apply straight from container by brush

DRYING TIME

Ensure the CEMIX SUPER PRIMER is fully dry prior to the application of subsequent products, allow approximately 20 minutes at 23°C and 50% relative humidity. Type of substrate being primed, porosity and climatic conditions will affect drying times, allow longer for lower temperatures or high relative humidity.



Scan to see CEMIX videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

SUPER PRIMER

COVERAGE

One litre will cover approximately 6 - 10m² depending on porosity of the surface and the method of application.

SHELF LIFE

A shelf life of 12 months is expected when stored in a dry place in original unopened packaging, at 23°C and 50% relative humidity.

If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.

WARNING

HAZARD STATEMENTS

- Causes eye irritation

PREVENTION

- Wash all exposed external body areas thoroughly after handling

RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

STORAGE

- Not Applicable

DISPOSAL

- Not Applicable

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring