



MORE THAN CONCRETE



CARPET ADHESIVE

FAST GRABBING ADHESIVE SUITABLE FOR MOST CARPETS

AVAILABLE SIZES: 1kg | 2kg | 4kg



CURING TIME



WATER
WASHUP



NON
FLAMEABLE



ECO
FRIENDLY



SCAN FOR
DETAILS

DESCRIPTION

CEMIX® CARPET ADHESIVE is a ready to use, adhesive which is specifically formulated for the installation of commercial and domestic carpet floor coverings. It has high initial grab and is ideal for bonding carpets to a variety of substrates. It is non-flammable, low odour, eco-friendly, water based formulation which is easy to apply. It contains an anti microbial.

SUBSTRATE PREPARATION

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive from bonding. New concrete should be left with a wood float finish and sufficiently aged for a minimum of 28 days. Shiny smooth surfaces on old concrete should be acid etched or scabbled. Then use Cemix cement screeds/floor levelers/renders and they must be allowed to cure for a minimum of 7 days. All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement, which may cause cracking. It is recommended to seal/prime surfaces.

Prime using Cemix Wall & Floor Primer undiluted using a roller or a brush and wait until it is tacky before applying this adhesive. Surfaces treated with waterproof membranes or some curing agents should be skimmed with a minimum of 3mm of a proprietary cementitious underlayment according to manufacturer's recommendations.

PLEASE ENSURE THERE IS NO RISING DAMP AS THIS WILL LEAD TO DELAMINATION. For further information, contact the CemixTechnical support.

MIXING

No mixing required. Just stir and use straight from the container.

APPLICATION

Spread adhesive with a notched trowel. Adhesive must be allowed to tack-up before floor covering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floor covering into the adhesive. When the floor covering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking every few minutes thereafter. Once the floor covering has been laid, they must NOT be trafficked upon or disturbed for a minimum of 24 hours at 20 °C. Allow 48 hours if temperatures fall below 20 °C or fixing over non porous substrates.

CLEANING

Clean all tools with water & brush immediately after use.

COVERAGE

FLOOR COVERING	TROWEL SIZE	COVERAGE
SMOOTH BACKED CARPET	2.4mm V notch trowels	4m ² per L
TEXTURE BACKED CARPET	3.2mm V notch trowels	3m ² per L
FOAM/FIBRE BACKED CARPET	1.6mm V notch trowels	5m ² per L

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

2/2

CARPET ADHESIVE

PREVENTION

- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing mist/vapours/spray
- Contaminated work clothing should not be allowed out of the workplace

RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention


DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring