



MORE THAN CONCRETE



FLOOR LEVELLER

MIX & POUR SELF-LEVELLING SYSTEM FOR DOMESTIC AND COMMERCIAL USE

AVAILABLE SIZES: 5kg | 10kg | 20kg

20
MINS

WORK TIME

3
HOURS

SET TIME



JUST ADD
WATER



SCAN FOR
DETAILS

DESCRIPTION & USES

CEMIX® FLOOR LEVELLER is an easy to use self leveller, just mix the product with water and pour the slurry on the floor surface. The slurry will level itself. It is supplied as a pre-blended, dry powder designed for application at thickness between 3 - 30 mm in one operation. Normal application thickness is 6 - 8 mm. Not self levelling below 6mm, needs to be manually troweled to level. CEMIX FLOOR LEVELLER is designed as an underlayment screed for use on concrete floor, prior to tiling, carpeting and to cover under floor heating coils.

ADVANTAGES

CEMIX FLOOR LEVELLER enables fast-track floor levelling and in normal conditions access onto the floor is available after 1 - 3 hours and the final flooring can be laid after 7 days (for a 10 mm layer) providing that the substrate is suitably dry. The obtained surface is so smooth that vinyl or carpet can be laid directly onto it and at the same time, provides a durable surface for use in commercial and domestic areas. CEMIX FLOOR LEVELLER combines rapid hardening and self-flowing properties with low shrinkage.

SUBSTRATE

CEMIX FLOOR LEVELLER is principally designed for application on concrete or structurally firm substrates. Any movement joints must be maintained as joints in the new surface.

SURFACE FINISH

In appearance, CEMIX FLOOR LEVELLER can be compared to ordinary concrete flooring. As an underlayment, CEMIX FLOOR LEVELLER is compatible with most commonly used adhesives and soft floor finishes as well as with hardwood flooring, ceramic tiles and athletic flooring.

PREPARATION

The surface to be treated must be hard, sound and free from surface contamination. All dust and debris should be vacuumed from the surface. Concrete laitance and old coatings should be removed mechanically. Concrete contaminated by oil or grease may require a degreaser.

PRIMING

CEMIX MULTIBOND should be applied to the prepared surface at 1 litre per 8m² on smooth concrete or 1.5 litres per 8m² on porous substrates using a soft brush and allowed to become tacky before the CEMIX FLOOR LEVELLER application.

MIXING AND APPLICATION

Add approximately 2 litres of clean water in a pail and slowly add 10kg powder while mixing vigorously, preferably with a mechanical mixer. Mixing time is between 3 - 4 minutes depending on the type of mixing equipment used. CEMIX FLOOR LEVELLER should be used within 20 minutes. The mixed material should be in slurry form and poured onto the surface while moving across the surface at a constant pace when a screed of uniform thickness is required.

Levels may be corrected by applying greater or lesser amounts of material as required, and falls may be maintained by pumping from the higher to the lower end. The freshly applied material may be lightly troweled with a serrated steel spatula to assist dissipation of surface bubbles and lines. The semi-hardened material may easily be formed or cut allowing any necessary adjustments to be made.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

2/2

FLOOR LEVELLER

COVERAGE

Depending on the surface to be treated. Normal approximately 10 kg of dry powder per 2m², corresponding to a layer of 3 mm thickness, is required. Dry powder consumption is 1.7 kg per mm thickness per square metre.

If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.

DANGER

HAZARD STATEMENTS

- Causes skin irritation
- Causes serious eye damage
- May cause respiratory irritation

PREVENTION

- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fumes

RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF ON SKIN: Wash with plenty of soap and water
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- If skin irritation occurs: Get medical advice/attention

STORAGE

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring