



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

1/2



FLOOR REPAIRER

HIGH STRENGTH RAPIDSET REPAIR MORTAR FOR CRACKS, HOLES AND IMPERFECTIONS

AVAILABLE SIZES: 5kg | 10kg

10
MINS

WORK TIME

30MPa

STRENGTH
AT 28 DAYS



SCAN FOR
DETAILS

DESCRIPTION

CEMIX® FLOOR REPAIRER is a one component, polymer modified, cementitious high strength powder, specifically designed for the patching and repair of floor surfaces. It contains especially graded fine aggregates and admixtures, scientifically proportioned to give an ultra-fine mix.

SUITABLE PROJECTS

CEMIX FLOOR REPAIRER can be used as a thin protective coating on concrete, mortar and masonry surfaces. It is ideal for honeycombed or surface damaged concrete and can be used for repairing formwork imperfections. It can also be used for creating falls in surfaces. CEMIX FLOOR REPAIRER can be applied from 1mm - 20mm in thickness.

ADVANTAGES

- Patches and repairs concrete flooring surfaces
- Fast setting and rapid hardening
- Ultra smooth finish
- Single component pre-blended powder - simply add water and mix
- Can be feather finished – down to 1mm
- Excellent bond strength with good substrate adhesion
- High resistance to water and chloride ion penetration
- Can be used for interior or exterior

PREPARATION

Thoroughly clean the area to be coated so as to remove all loose and deleterious materials and debris, including all dust, dirt and oil. All surfaces should be roughened, uncoated, clean and have an open capillary structure.

Any existing paints or coatings must be completely removed. Before application, ensure that the surface is primed with CEMIX MULTIBOND.

MIXING

The mix ratio for CEMIX FLOOR REPAIRER is 1kg of product to 220ml water.

APPLICATION

Pour the required amount of clean fresh water into a suitable mixing container. Next, slowly add the prescribed amount of CEMIX FLOOR REPAIRER powder being careful not to allow the material to clump, while mixing with a slow speed electric drill and mixing paddle. Mix thoroughly until a smooth, lump free consistency is achieved. Normally a mixing time of 3 minutes at 20°C is recommended. Apply the mixed CEMIX FLOOR REPAIRER to the prepared substrate by steel trowel from 1mm to 20mm thickness and allow to partially set before finally trowelling to a smooth finish. As CEMIX FLOOR REPAIRER is fast setting, only mix as much product as can be used in 10 minutes.

YIELDS

Approximately 5m² at 1mm thickness.

If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

FLOOR REPAIRER

DANGER



HAZARD STATEMENTS

- May be harmful if swallowed
- May be harmful if inhaled
- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction
- May cause respiratory irritation

PREVENTION

- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fumes
- Contaminated work clothing should not be allowed out of the workplace

RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF ON SKIN: Wash with plenty of soap and water
- IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell
- If skin irritation or rash occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

STORAGE

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION.



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
 AUCKLAND NEW ZEALAND
 0800 ASK CEMIX | +64 09 636 1000
 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see CEMIX videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring