



MORE THAN CONCRETE



# QUICK FINISH

## FINISH COAT SMOOTHING COMPOUND

AVAILABLE SIZES: 10kg | 20kg



RAPID DRYING



APPLY USING STEEL TROWEL



SCAN FOR DETAILS

### DESCRIPTION

Cemix® QUICK FINISH is a cement based smoothing compound designed to provide a smooth, permanent finish to a variety of internal substrates prior to the installation of floor coverings such as vinyl, carpet and ceramic tile. QUICK FINISH allows the installation of most floor coverings in as little as 20 minutes over concrete, wood, ceramic and quarry tile, all without the need for priming or additives. It is suitable for residential and commercial areas. QUICK FINISH mixes with water to provide a smooth, creamy mortar for easy application. Engineered around a self-drying cement based matrix, all of the mix water is chemically converted within the product. This unique technology eliminates flooring installation problems such as debonding, crumbling, mildew and staining.

### SURFACE PREPARATION

Concrete floors must be structurally sound, clean and free of dirt, dust, oil, curing and sealing compounds and any other surface contaminant which may act as a bond breaker. Where required, mechanically clean the floor using recommended preparation methods such as shotblasting, scarifying, diamond grinding, shaving or other acceptable methods to a suitable surface. Acid etching is not an acceptable method of cleaning the subfloor. Do not use solvents or sweeping compounds. Subfloor temperatures must be a minimum of 10°C.

### MIXING RATIO

Depending on application mix 4.5 - 5.0 litres of water to 10kg of QUICK FINE FINISH powder, or by volume; 1 part of water to 2 parts of QUICK FINISH powder.

### MIXING

Cemix repair products react and harden quickly when mixed with water. Thorough mixing in the shortest possible time is essential

to ensure a lump free, slump resistant mortar. Always mix the powder into the water. Mechanical mixing using a mixing paddle and electric drill will produce a creamier, smoother consistency. Do not overwater.

### INSTALLATION

QUICK FINISH is easily applied to any prepared surface using a steel trowel. Apply sufficient pressure to fill all defects and to fine the product into the subfloor surface. It is not necessary to leave a minimum thickness on the substrate. Use the least amount possible to obtain the desired smoothness.

### THICKNESS

QUICK FINISH can be applied from a true fine edge up to 3mm in one application. POT LIFE Approximately 20 minutes at 20°C. Pot life will be extended in cooler conditions and shortened in warmer conditions. Mix only the amount that will be used immediately to avoid waste.

### INSTALLATION OF FLOORING

As soon as the QUICK FINISH can be walked on without damaging the surface (approx 15 minutes), floor coverings such as vinyl, carpet and ceramic tile can be installed. When installing a skim coat of QUICK FINISH over non-porous surfaces such as ceramic tiles or vinyl, always refer to the adhesive supplier for their recommended installation procedure.

### POT LIFE

Approximately 20 minutes at 20°C. Pot life will be extended in cooler conditions and shortened in warmer conditions. Mix only the amount that will be used immediately to avoid waste.



Scan to see CEMIX videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

# QUICK FINISH

## COVERAGE

The unique formulation of QUICK FINISH produces coverage 3 times that of sanded products. A 10kg unit will cover 20m<sup>2</sup> at 1mm thickness. When skim coating over concrete, coverage is up to 35m<sup>2</sup> and over plywood 70m<sup>2</sup> can be achieved.

## STORAGE

QUICK FINISH has a shelf life of 12 months if stored in dry conditions in unopened packaging.

**If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.**

**DANGER**



## HAZARD STATEMENTS

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction
- May cause respiratory irritation

## PREVENTION

- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fumes
- Contaminated work clothing should not be allowed out of the workplace

## RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

## STORAGE

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

## Disposal

- Dispose of contents/container in accordance with local regulations

## DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

## SCAN QR CODE FOR MORE PRODUCT INFORMATION:



## CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring