



MORE THAN CONCRETE



# VINYL ADHESIVE

## FAST GRABBING ADHESIVE SUITABLE FOR MOST VINYL FLOORING

AVAILABLE SIZES: 1kg | 2kg | 4kg

|              |              |               |              |                  |
|--------------|--------------|---------------|--------------|------------------|
|              |              |               |              |                  |
| SERVICE TIME | WATER WASHUP | NON FLAMEABLE | ECO FRIENDLY | SCAN FOR DETAILS |

### DESCRIPTION

Cemix® VINYL ADHESIVE is a ready to use water based adhesive which is specifically formulated for the installation of commercial and domestic vinyl floor coverings. It has high initial grab and is ideal for bonding carpets to a variety of substrates. It is non-flammable, low odour, eco-friendly, water based formulation which is easy to apply. It contains an anti microbial.

### SUBSTRATE PREPARATION

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive from bonding. New concrete should be left with a wood float finish and sufficiently aged for a minimum of 28 days. Shiny smooth surfaces on old concrete should be acid etched or scabbled. Then use Cemix cement screeds/floor levelers/renders, and they must be allowed to cure for a minimum of 7 days. All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement, which may cause cracking. It is recommended to seal/prime surfaces.

Prime using Cemix Wall & Floor Primer undiluted using a roller or a brush and wait until it is dry before applying this adhesive. Surfaces treated with waterproof membranes or some curing agents should be skimmed with a minimum of 3mm of a proprietary cementitious underlayment according to manufacturer's recommendations.

**PLEASE ENSURE THERE IS NO RISING DAMP AS THIS WILL LEAD TO DELAMINATION.** For further information, contact the Cemix Technical support.

### MIXING

No mixing required. Just stir and use straight from the container.

### APPLICATION

Spread adhesive with a notched trowel. Adhesive must be allowed to tack-up before floor covering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floor covering onto the adhesive. When the floor covering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking every few minutes thereafter.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight, prior to the adhesive setting. Once the floor covering has been laid, they must NOT be trafficked upon or disturbed for a minimum of 24 hours at 20 °C. Allow 48 hours if temperatures fall below 20 °C or fixing over non porous substrates.

### COVERAGE

| FLOOR COVERING | TROWEL SIZE          | COVERAGE              |
|----------------|----------------------|-----------------------|
| VINYL TILES    | 1.6mm V notch trowel | 5m <sup>2</sup> per L |

### CLEANING

Clean all tools with water & brush immediately after use.

**Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.**



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

# VINYL ADHESIVE

**DANGER**



## HAZARD STATEMENTS

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction

## PREVENTION

- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing mist/vapours/spray
- Contaminated work clothing should not be allowed out of the workplace

## RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention

## DISPOSAL

- Dispose of contents/container in accordance with local regulations

## DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the re-quirements of the Consumer Guarantees Act.

## SCAN QR CODE FOR MORE PRODUCT INFORMATION



### CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
 AUCKLAND NEW ZEALAND  
 0800 ASK CEMIX | +64 09 636 1000  
 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see CEMIX videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring