



MORE THAN CONCRETE

0800 ASK CEMIX

CONCRETE & MORTARS

February 2020 | Page 1

CEMPLASTER

FOR SOLID PLASTERING FOR LAYERS UP TO 12MM

AVAILABLE SIZE: 20kg | 30kg



SCAN FOR DETAILS



DESCRIPTION:

Cemix® Cemplaster can be used for plastering over lath wall, block work, brickwork and tilt slab substrates. Cemix® Cemplaster displays a high level of workability and coverage; it resists sagging, cracking and shrinkage. The results of Cemix® Cemplaster are assured only if it is applied on a key coat of Cemix® Cemsplash.

TYPICAL APPLICATION/USES:

- Applications where a solid wall plaster in layers up to 12mm are required.
- Cemix® Cemplaster is especially suited for professional plasterers.

COMPOSITION AND MATERIALS:

Cemix® Cemplaster consists of a uniformly blended, properly proportioned mixture of sands, Portland cement and other admixtures approved for use in mortar to improve water retention, workability and performance of the product.

SUBSTRATE PREPARATION:

Substrates should be clean & free from all contaminants, loose particles, coatings, curing compounds, dirt, mould, oil etc. Substrates must be sound, rough & dampened to ensure a good bond.

MIXING:

Please ensure that Cemix® Cemsplash has been applied to the substrate to be plastered. Ensure that the key coat has been given at least 48 hours to cure and harden. The results of Cemix® Cemplaster are assured only if it is applied on a key coat of Cemix® Cemsplash.

LIMITATIONS:

- Cemsplash should be used in conjunction with Cemplaster as a key coat to ensure a good bond.

APPLICATION:

Empty contents of Cemix® Cemplaster bag into a mechanical mixer. Add water gradually, mixing until a smooth mix is achieved. Under ideal conditions a bag of 30kg bag would require 4.5 – 5L of water and a 20kg bag would require approx. 3 - 3.4L of water. Mix only until you get the desired consistency and don't over mix. Pour in a barrow and then apply. Prior to applying Cemix® Cemplaster please ensure the key coat is moist enough. Do not let the mix stand unused for long periods of time. Depending on the weather, please ensure that the surface is kept moist for 7 days.

COVERAGE:

Under ideal conditions one 30kg bag will cover 2.4m² approx. at 10mm - 12mm thickness. A 20kg bag will cover approx. 1.6m² at 10mm - 12mm thickness.

PACKAGING:

Cemix® Cemplaster comes in 20kg and 30kg bags.

STORAGE & SHELF LIFE:

Store Cemix® Cemplaster in a cool dry area and use within six (6) months.

CLEANING:

Clean all tools with water & brush immediately after use.

TECHNICAL DATA:

STANDARDS	NZS 3113, NZS 3103 NZS 4251 for plastering
APPEARANCE	Sand / Cementitious
APPLICATION TEMP:	5 °C - 30 °C

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



CEMPLASTER

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER



HAZARD STATEMENTS:

- Causes skin irritation
- Causes serious eye damage
- May cause an allergic skin reaction
- May cause damage to organs
- May cause damage to organs through prolonged or repeated exposure

SAFETY INSTRUCTIONS:

- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.

INGREDIENTS:

Graded Sand, 14808-60-7, 60-80%
 Portland Cement, 65997-15-1, 25-28%
 Ingredients determined not to be hazardous, Not Available, 4-5%

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
 AUCKLAND NEW ZEALAND
 0800 ASK CEMIX | +64 09 636 1000
 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see CEMIX videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

CEMPLASTER



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring