



MORE THAN CONCRETE



PAVSEAL

PENETRATING CLEAR WATERPROOFING SEALER

AVAILABLE SIZES: 1L, 4L, 20L, 200L



SCAN FOR DETAILS



NON TOXIC



UV STABLE



ECO FRIENDLY

DESCRIPTION

CEMIX PAVSEAL is a stain resistant water based penetrating and film forming clear weatherproofing sealer. It is based on silane modified nano particle size, self-cross linking hybrid technology and can be effectively used for impregnating and sealing a variety of pavers. It provides adhesion, penetrating and sealing properties on various substrates because of the nano dense self-cross linking particles. There is little or no impairment of the paver's ability to breathe and exhibits a good MVTR (moisture vapour transmission rate). It can be successfully applied on slightly damp pavers, but surface dry pavers. The application does not produce any discolouration of the surface and is suitable for weatherproofing and sealing a wide variety of absorbent surfaces and not suitable for very dense substrates like marble and granite. It can also be used on timber decks, outdoor furniture, timber wall cladding, clay roof tiles, fibre reinforced cement sheets etc.

TYPICAL APPLICATION/USES

For sealing a variety of pavers
It can also be used on timber decks, outdoor furniture, timber wall cladding, clay roof tiles, fibre reinforced cement sheets etc

ADVANTAGES

- Environmentally friendly green product
- Hybrid sealer – penetrates as well as coats (thin film).
- Exhibits a high degree of stain resistance
- Chemically resistant and non toxic
- UV stable – will not go yellow over time

SUBSTRATE PREPARATION

Ideally this sealer should be applied on new freshly laid pavers. The paver surfaces should be water blasted and made clean, free from grease, loose particles, dirt, paint, curing compounds

etc. Moss or algae growth should be removed with a suitable treatment and washed with clean water.

APPLICATION

Shake or stir thoroughly before use. Always test apply on an area first and approve look and feel. CEMIX PAVSEAL should be applied without diluting in two coats to ensure complete coverage and saturation of the paver substrate. Apply with garden sprayer, roller or brush. Depending on the porosity of the pavers – a coverage of approximately 5m² – 14m² per litre can be achieved.

GOLDEN RULE

There is no one sealer for all types of surfaces. The golden rule is to never apply more product than is being absorbed into the surface you are sealing. If product is pooling on the surface, brush the excess off. Do not let product pool on surface as this can result in excessive build up which is difficult to remove. If you feel no product or very little is being absorbed, stop, and seek technical advice from CEMIX. Always do a small test area first and approve look and feel.

TECHNICAL DATA

- Appearance – Milky translucent white emulsion
- Application Temp – 5°C – 30°C
- Yield / Coverage – 5m² – 14m² per litre
- Packaging – 1L, 4L, 20L and 200L
- Type Anionic, Silane Modified Dispersion
- Appearance Milky, translucent white emulsion
- Ph 7.5 to 9.0
- Density @ 2°C 1.06Kg/Lt
- Odour Acrylic

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

PAVSEAL

LIMITATIONS

Due to film forming properties, may become slippery in wet areas.

STORAGE / SHELF LIFE

Twelve (12) months when stored in unopened, original containers. Storage area should not be exposed to extreme temperature. Do not expose to direct sunlight in storage.

CLEANING

Clean all tools with water & brush immediately after use.

If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.

DANGER



HAZARD STATEMENTS

- Harmful if swallowed
- Causes skin irritation
- Causes serious eye damage
- Harmful to aquatic life with long lasting effects

PREVENTION

- Wear protective gloves/protective clothing/eye protection/face protection
- Do not eat, drink or smoke when using this product
- Avoid release to the environment

RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- IF ON SKIN: Wash with plenty of soap and water
- Rinse mouth

STORAGE

- Not Applicable

DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION:



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring