



MORE THAN CONCRETE



# POTTERY SEALANT

## GARDEN ORNAMENT SEALER

AVAILABLE SIZES: 500ML



SCAN FOR  
DETAILS



UV STABLE



ECO  
FRIENDLY



NON TOXIC



WEATHER  
RESISTANT

### DESCRIPTION

CEMIX POTTERY SEALANT is a clear satin finish water based eco friendly penetrating water resistant sealer. It is non-toxic and resists mould and lichen. It is based on silane modified nano particle size, self-cross linking hybrid technology and can be effectively used for impregnating and sealing a variety of garden ornaments, garden pots, bird baths, reconstituted stone & carved stone features and other porous garden objects. It has outstanding adhesion, penetrating and sealing properties on various substrates. The application does not produce any discolouration of the surface and is suitable for water resistant and sealing a wide variety of absorbent surfaces and not suitable for very dense natural stone, especially marble and granite. It can also be used on timber decks, outdoor furniture, timber wall cladding and cured decorative water based coatings that do not show signs of chalking.

### TYPICAL APPLICATION / USES

- Bird Baths
- Garden Ornaments
- Garden Pots
- Reconstituted stone
- Porous garden objects
- Carved stone

### ADVANTAGES

- Environmentally friendly green product
- Non toxic – can be used for Bird Baths
- Fast drying and a clear satin finish
- Can be applied on damp or moist substrates
- Hybrid sealer – penetrates as well as coats
- Exhibits a high degree of stain resistance
- Chemically resistant
- UV stable – will not go yellow over time

- Weathering resistant
- Resistant to dirt pick up
- Kills and resists micro-organisms
- Simple application – spray bottle packaging

### SUBSTRATE PREPARATION

The surfaces should be water blasted and made clean, free from grease, loose particles, dirt, paint, curing compounds etc. Moss or algae growth should be removed with a suitable treatment and washed with clean water. Always test apply on an area first and approve look and feel.

### APPLICATION

Shake or stir thoroughly before use. Always test apply on an area first. CEMIX POTTERY SEALANT should be applied without diluting in two coats to ensure complete coverage and saturation of the substrate. Apply straight from the spray pack and the sealer will dry in about 20mins at 25°C. On high absorbent surfaces, repeat or increase the rate of application until surface is completely saturated. Re-application at a later date is possible provided the substrate is clean. Depending upon the porosity of the substrate – coverage of 5m<sup>2</sup>/L should be achieved.

**NOTE:** There is not a sealer suitable for all types of pavers, tiles, or other surfaces. Never apply more product than is being absorbed into the surface you are sealing. If product is pooling on the surface, brush the excess off. If you feel no product or very little product is being absorbed, stop and seek technical assistance. Always do a test area first to approve the look and feel before doing the entire area. Ensure there is no rising damp as this will make the sealer surface cloudy. Over application can make the surface slippery especially when wet.



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring



MORE THAN CONCRETE

Page - 2

# POTTERY SEALANT

## CURING

Cure concrete after it has set using standard curing methods.

## TECHNICAL DATA

- Appearance – Milky, translucent white emulsion
- Application Temp – 5 – 30 °C
- Yield / Coverage – 5m<sup>2</sup>/L
- Packaging – 1.2L Spray bottle.
- SG – 1.01
- TG – 55 °C
- Type – Anionic, Silane Modified Dispersion
- Ph – 7.5 to 9.0
- Odour – Acrylic
- Minimum Application Temp – >5 °C
- Density @ 20 °C – 1.06Kg/Lt

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

## AGITATIONS

Shake both concentrate & diluted product thoroughly before using them taking care not to contaminate them.

## CLEANING

Spray or roller equipment should be washed out immediately after use with water.

## STORAGE / SHELF LIFE

Twelve (12) months when stored in unopened, original containers. Storage area should not be exposed to extreme temperature. Do not expose to direct sunlight in storage.

**If medical advice is needed, have product container or label at hand. Read label before use. Keep out of reach of children.**

**DANGER**

## HAZARD STATEMENTS

- Harmful if swallowed
- H315 Causes skin irritation
- H318 Causes serious eye damage
- Harmful to aquatic life with long lasting effects

## PREVENTION

- Wear protective gloves/protective clothing/eye protection/face protection
- Do not eat, drink or smoke when using this product
- Avoid release to the environment

## RESPONSE

- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- Take off contaminated clothing and wash before reuse
- **IF SWALLOWED:** Call a POISON CENTER or doctor/physician if you feel unwell
- **IF ON SKIN:** Wash with plenty of soap and water
- Rinse mouth

## STORAGE

- Not Applicable

## DISPOSAL

- Dispose of contents/container in accordance with local regulations

## DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

## SCAN QR CODE FOR MORE PRODUCT INFORMATION:



## CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061  
AUCKLAND NEW ZEALAND  
0800 ASK CEMIX | +64 09 636 1000  
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNZ



Pinterest/CemixNZ



YouTube/CemixVideos



Scan to see  
Cemix videos

Visit Cemix's wide range of products at [www.cemix.co.nz](http://www.cemix.co.nz)

Concrete & Mortars   Repairs & Grouts   Admixtures   Decorative Sealers   Waterproofing   Tiling & Flooring