



MORE THAN CONCRETE



COLOURED GROUT

FLEXIBLE COLOURED GROUT FOR USE WITH MOST TYPES OF MOSAIC & CERAMIC TILES

.....
AVAILABLE SIZE: 2kg | 5kg



SCAN FOR DETAILS

DESCRIPTION:

Cemix® Coloured Grout is a flexible smooth finish cementitious grout designed for use with most types of mosaic, ceramic tiles and natural stone applications in internal or external wall and floor grouting applications for joints between 1mm - 8mm. The grout also contains a biocide, which provides it with a resistance to a broad spectrum of moulds and bacteria. When grouting swimming pools or over timber floors and substrates where movement is expected or for superior performance in general applications, mix the grout with Cemix® Tile bond latex primer & additive as a total water replacement. Please contact Cemix® Technical support for more details.

TYPICAL APPLICATION/USES:

For use with most types of mosaic, ceramic tiles and natural stone applications internal or external wall and floor grouting applications for joints between 1mm - 8mm.

ADVANTAGES:

- Flexible
- Smooth finish
- May be used in swimming pools when used in conjunction with Cemix® Tile Bond Latex as an additive.

JOINT PREPARATION:

Before commencing grouting, ensure the tile adhesive has set firmly. This usually requires 24 hours weather dependent. Remove any spacer lugs, rake-out any excess adhesive and ensure the joints are free from dust and all other friable loose materials and contaminants likely to prevent the grout bonding. Dampen the joints(not wet) before commencing to grout. For further information, contact the Cemix® Technical support 0800 ASK CEMIX.

MOVEMENT JOINTS

Movement joints must be incorporated at the design stage and should go right through the tile adhesive bed to the background and be kept free from dirt and adhesive droppings.

1. Add approx. 200 - 240ml of clean water per kilo of grout to a bucket.
2. Sprinkle the grout powder slowly into the water, mixing constantly until a thick creamy toothpaste consistency is achieved - with no lumps.
3. Allow to stand for 5 minutes and re mix. Then the grout is ready to use.
4. When grouting swimming pools or over timber floors and substrates where movement is expected or for superior performance in general applications, mix the grout with Cemix® Tile bond latex primer & additive as a total water replacement.
5. DO NOT aerate the mix by stirring over vigorously or for too long. The mix should be stiff enough to keep its shape when spread with a notched trowel. Always add powder to water and not vice versa.

APPLICATION:

Apply the grout using a rubber float or squeegee in a diagonal motion, ensuring that the grout is compacted into the entire depth of the joint. Remove the excess grout from the surface of the tiles using the float or squeegee, ensuring that the grout in the joints is not dislodged. Allow the grout to firm up in the joints before cleaning the tiles with a wet sponge or cloth. Regularly rinse the sponge/cloth to ensure proper wiping of the grout haze on the tiles.



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

February 2020 | Page 2

COLOURED GROUT

CURING:

Once the tiles have been laid they will reach full cure after 14 days after which the grout joints can be immersed in water (swimming pools). Allow longer for lower temperatures, dense tiles or high relative humidity.

TECHNICAL DATA:

SETTING FINAL	Approx 2 hours
APPEARANCE	Cementitious powder
BULK DENSITY	112lbs/ft (1.81 kg/l)
POTABLE WATER	Suitable
POT LIFE	30 minutes
<i>The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.</i>	

COVERAGE:

The coverage of the grout will vary depending upon the texture, size and thickness of the tile and the width of the grout joint. Use the table below as a general guide:

TILE SIZE (MM) L X W X D	JOINT WIDTH			
	1.5MM	3MM	5MM	8MM
25 x 25 x 4	4.5m ²	2.3m ²	1.4m ²	0.8m ²
100 x 100 x 8	9.1m ²	4.5m ²	2.7m ²	1.7m ²
200 x 200 x 8	18.1m ²	9.1m ²	5.4m ²	3.4m ²
330 x 330 x 9	27.2m ²	13.2m ²	7.9m ²	5.0m ²

PACKAGING:

Cemix Coloured Grout is available in 2kg or 5kg boxes

STORAGE & SHELF LIFE:

Cemix Coloured Grout can be stored for up to twelve (12) months - unopened containers in dry weatherproof storage.

CLEANING:

Clean all tools with water & brush immediately after use.

Read Label Before Use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

DANGER:**HAZARD STATEMENTS:**

- Causes skin irritation.
- Causes serious eye damage.
- May cause an allergic skin reaction.
- Causes damage to organs.
- Causes damage to organs through prolonged or repeated exposure.

PREVENTION:

- Do not breathe dust/fume.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing should not be allowed out of the workplace.

INGREDIENTS:

Graded Sand, 14808-60-7, 30-60%;
Portland Cement, 65997-15-1, 30-60%;
Ingredients determined not to be hazardous, N.A, 10-40%



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

0800 ASK CEMIX

TILING & FLOORING

February 2020 | Page 3

COLOURED GROUT

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it at no cost in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring