



MORE THAN CONCRETE



0800 ASK CEMIX

WATERPROOFING

AQUASTOP

CEMENT BASED WATERPROOF SLURRY COATING SYSTEM

AVAILABLE SIZES: 2kg | 4kg | 10kg | 20kg



1
HOUR

WORK TIME

7
DAYS

SERVICE TIME



JUST ADD
WATER



SCAN FOR
DETAILS

DESCRIPTION

CEMIX® AQUASTOP is a cement based powder which is white in colour, however can be tinted with CEMIX oxides or painted over if required. It can be applied with a brush, roller, sprayed or trowelled to any correctly prepared concrete or masonry surface. CEMIX AQUASTOP is recommended as an effective, decorative waterproofing coating on interior or exterior concrete, masonry, concrete block, mortar, plaster, stucco and brick. It is not designed to be applied over bitumen, tar, oil, rubber, plastic, metal or previously painted concrete surfaces.

SUITABLE PROJECTS

- As a membrane waterproofing solution for both the positive (e.g. outside of the house) and negative (e.g. inside of the house) face of a wall/floor or similar structure

FEATURES

- Resists hydrostatic pressure – Provides a water repellent surface
- Can be applied to a damp surface
- Just add water
- Chemically bonds to the surface - will not chalk or dust
- Inhibits mould and or fungus growth
- Can be used as a filler prior to a blanket application

SUBSTRATE PREPARATION

Thoroughly clean the area to be coated so as to remove all loose and deleterious materials and debris, including all dust, dirt and oil. If necessary, the whole area may be water blasted to assist with adequate preparation, though extreme care must be taken to ensure this does not damage the substrate. The substrate surface should ideally be dry though this is not critical. If it is too wet however you may experience difficulties in applying the CEMIX AQUASTOP.

APPLICATION

CEMIX AQUASTOP can first be used as a filler for any large cracks or hollows, using a suitable clean dry sand added at a ratio of 1 part CEMIX AQUASTOP to two parts sand, mixed with a small amount of water.

CEMIX AQUASTOP must be applied within one hour of mixing. Apply to the surface thoroughly and evenly ensuring any air bubbles or pin holes are brushed out.

Two coats are recommended. Apply the second coat at right angles to the first. The second coat may be applied any time 6 hours after the first coat.

Do not apply CEMIX AQUASTOP if rain is expected during or immediately after application. High winds, direct sunlight or excessive heat may cause CEMIX AQUASTOP to cure too quickly. It is recommended to apply to exterior work while it is shaded.

DRYING & CURING TIME

Ambient temperatures will affect the initial drying time of CEMIX AQUASTOP. In general, 7 days will be required before it can effectively resist the passage of water.

MIXING

Place approximately 900ml of clean fresh tap water per kg of CEMIX AQUASTOP powder in to a bucket or similar container. Next add the CEMIX AQUASTOP to the water at the appropriate dose rate while stirring constantly with a flat stick until a smooth and creamy paint like consistency is achieved. Add further water if required however do not exceed more than 1.1 litres per kg of CEMIX AQUASTOP powder in total. Allow to stand for 10 minutes then stir again before applying. If required, stir occasionally while using to prevent settling.



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

AQUASTOP

If desired, a small amount of CEMIX oxide can be added to tint the mixture. This must be mixed in at the outset and at a ratio of no more than 40 grams per kg of CEMIX AQUASTOP.

CURING

Do not apply outside if rain is expected during or immediately after application. High winds, direct sunlight or excessive heat may cause CEMIX AQUASTOP to cure too quickly. It is recommended to paint exterior work while it is shaded.

LIMITATIONS

It cannot be applied over bitumen, tar, oil, rubber, plastic, metal etc. surfaces or previously painted concrete surfaces or any other existing coating. Watch the YouTube video and contact CEMIX technical if you require further assistance. Follow all safety instructions on the pack; wear gloves, mask and especially eye protection. Avoid contact with skin.

STORAGE & SHELF LIFE

CEMIX AQUASTOP is best stored out of direct sunlight for Twelve (12) months.

CLEANING UP

Clean all tools with water and a brush immediately after use.

YIELDS

- First coat on concrete block or similar surface: 2 - 3m² per kg
- Second coat on concrete block or similar surface : 3.5 - 4.5m² per kg
- First coat on stucco and rough surfaces: 1.5 - 2.5m² per kg
- Second coat on stucco and rough surfaces: 3.0 - 4.0m² per kg

TECHNICAL DATA

APPLICATION TEMP	5-30°C
APPEARANCE	White powder un-mixed

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

If medical advice is needed, have product container or label at hand.

Read label before use.

Keep out of reach of children.

DANGER

HAZARD STATEMENTS

- Harmful if swallowed
- Causes skin irritation
- Causes serious eye damage
- May cause cancer
- May cause damage to organs
- May cause respiratory irritation
- May cause damage to organs through prolonged or repeated exposure
- Harmful to terrestrial vertebrates



PREVENTION

- Obtain special instructions before use
- Do not breathe dust/fume/gas/mist/vapours/spray
- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection
- Use personal protective equipment as required
- Do not eat, drink or smoke when using this product

EMERGENCY RESPONSE

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- IF exposed or concerned: Get medical advice/attention
- IF exposed or if you feel unwell: Call NZ NATIONAL POISONS CENTRE (0800 764 766) or doctor/physician
- Take off contaminated clothing and wash before reuse
- IF SWALLOWED: NZ NATIONAL POISONS CENTRE (0800 764 766) or doctor/physician
- IF ON SKIN: Wash with plenty of soap and water
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Rinse mouth
- If skin irritation occurs: Get medical advice/attention

STORAGE

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

DISPOSAL

- Dispose of contents/container in accordance with local regulations



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

AQUASTOP

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it at no cost in accordance with the requirements of the Consumer Guarantees act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring