



BITUPATCH POTHOLE REPAIRER

PERMANENT REPAIR FOR POTHOLES AND ASPHALT REINSTATEMENTS IN ROADS, CARPARKS AND DRIVEWAYS

AVAILABLE SIZES: 20kg







DESCRIPTION & USES

CEMIX® BITUPATCH is a ready to use, no mixing required cold mix Bitumen asphalt for the repair of potholes in asphalt roads, driveways and paths. It is simply and easily placed directly from the bag in to the hole.

SUITABLE PROJECTS

- Potholes in all types of asphalt
- Speed humps
- CEMIX BITUPATCH can be applied between 5°C 30°C; however, for best performance, compac-tion and workability, use CEMIX BITUPATCH between air temperatures ranging from 21°C - 30°C.

FEATURES

- Ready to use
- Simple to install Clean / Pour / Compact
- No time spent waiting for curing
- Can be used in all weather conditions
- High performance
- Cost effective
- Permanent solution

APPLICATION POUR

Fill the hole with CEMIX BITUPATCH Make the middle slightly higher than the sides (this is called crowning) Depending on the size of the repair give yourself a 5 - 10mm crown This will counteract the subsidence caused by compacting.

COMPACT

For best results and performance, compact with a mechanical vibrating plate compactor or steel wheel roller Smaller areas can be compacted with any large heavy flat item such as large timber posts, compressed using a rubber mallet.

SUBSTRATE PREPARATION

Thoroughly clean the area to be filled so as to remove all loose and deleterious materials and de-bris. If possible create a vertical edge to the hole for the CEMIX BITUPATCH to butt up against.

LIMITATIONS

- CEMIX BITUPATCH can be applied between 5°C 30°C; however, for best performance, compac-tion and workability, use CEMIX BITUPATCH between air temperatures ranging from 21°C - 30°C.
- A vibratory steel wheel roller will always provide optimum results and performance; however, steel wheel or pneumatic rollers, compactor plates, wheel rolling, and hand tamping are also acceptable methods of compaction.

STORAGE & SHELF LIFE

Store CEMIX BITUPATCH in a cool dry area and use within 12 months.

CLEANING

Clean all tools with water and a still bristled brush immediately

If medical advice is needed, have product container or label at hand.

Read label before use.

Keep out of reach of children.



2/2



BITUPATCH

TECHNICAL DATA

APPLICATION TEMP	5-30°C
APPEARANCE	Black Tar

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.





HAZARD STATEMENTS

May cause drowsiness or dizziness

PREVENTION

- Use only outdoors or in a well-ventilated area
- Avoid breathing mist/vapours/spray

EMERGENCY RESPONSE

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- In all instances contact the NZ NATIONAL POISONS CENTRE (0800 764 766) or doctor/physician

STORAGE

- Store locked up
- Store in a well ventilated place. Keep container tightly closed

DISPOSAL

Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the re-guirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061 AUCKLAND NEW ZEALAND 0800 ASK CEMIX I +64 09 636 1000 WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos

