



GROUT HAZE REMOVER

100% BIO DEGRADABLE, PRE - MIXED, READY TO USE,
MILD ACID SOLUTION



500ml

APPLICATION:

CEMIX® GROUT HAZE REMOVER should be used to clean the surface after tiling and grouting have been done. Scrub the surface with a nylon bristled brush or a thick sponge, after applying the solution. Work in small areas only, flush with water immediately after brushing surface.

TECHNICAL DATA:

APPEARANCE:	Green Colour
APPLICATION TEMP:	5°C - 30°C
DENSITY @ 20°C:	1.07Kg/L
ODOUR:	Slight Vinegar odour

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

DESCRIPTION:

CEMIX® GROUT HAZE REMOVER is a non acid alternative to remove haze from the tiling after grouting. Using this product will clean all the dried spots and even hard water deposits. It is a biodegradable liquid that is non corrosive to skin but acts on the haze. The result is a nice and clean floor that you have worked for. It contains no acid and will not harm painted surfaces, tools, metal surfaces, plastic surfaces, or any type of plants or vegetation. It is easily neutralized and diluted with water. It is fast acting but not instantaneous, so correct application of the liquid to the material is the key to success.

NOTE: Pre mixed solution, Acidic in the way a lemon or orange is but dose not contain any acid.

TYPICAL APPLICATION/USES:

Cemix® Grout Haze Cleaner can be used for cleaning of flooring tiles, after grouting is done. This solutions gives a neat and clean look to your tiled floor.

ADVANTAGES:

- Acidic in the way a lemon or orange is, but does not contain any acid.
- 100% Biodegradable.
- Removed dried haze.
- Safe for use on coloured grouts.
- Removes hard water deposits & efflorescence.
- Water neutralised.

STORAGE:

Cemix® Grout Haze Cleaner can be stored for Twelve (12) months in original, unopened containers when stored in dry conditions between +5°C and +30°C. Keep containers closed in a well ventilated area when not in use. Do not expose to direct sunlight in storage.

PRECAUTION:

Prolonged exposure to paint or tiles may result in surface damage. Always ensure a test area is carried out before doing the entire surface.

SAFETY:

Avoid repeated and prolonged skin contact. Wear safety glasses to minimize the risk of splashes getting into the eyes. Wear plastic or rubber gloves if there is a risk of prolonged or repeated skin contact. Natural ventilation should be adequate under normal conditions of use.

FIRST AID:

Irrigate eyes & skin with plenty of water & seek medical advice immediately. If ingested, rinse mouth with water. Do not induce vomiting.

SPILLS AND LEAKS:

Keep out of sewers & storm water drains & dispose of any leftover material as trade waste in accordance with local authority guidelines.

DISCLAIMER:

Recommendations & advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, Cemix® Products LTD does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of Cemix® Products LTD. If you need advice concerning the use of suitability of this product for your particular application, please contact Cemix® Products LTD first.

CEMIX PRODUCTS LTD
19 ALFRED STREET
ONEHUNGA 1061
AUCKLAND
NEW ZEALAND

0800 ASK CEMIX
WWW.CEMIX.CO.NZ

