



MORE THAN CONCRETE



ROOF & GUTTER WATERPROOFER

MULTI-USE, FLEXIBLE, EXTERIOR GRADE, BRUSHABLE LIQUID RUBBER

AVAILABLE SIZES: 2kg | 4kg | 10kg

3-4
HOURS

SET TIME

7
DAYS

CURING TIME



WEATHER RESISTANT



UV STABLE



SCAN FOR DETAILS

DESCRIPTION

CEMIX® ROOF & GUTTER WATERPROOFER is a high performance elastomeric and flexible exterior grade brushable waterproofer with long term UV and weather resistance to exposed and permanently immersed areas. This versatile durable and tough weatherproof coating is able to withstand extreme weather conditions (hot & cold). Exterior protective coating for roofs, gutters, decks, steel, asbestos, aluminium, concrete, bricks, plywood, timber, fibre cement sheets, vertical wall facades and general surfaces exposed to the weather.

ADVANTAGES

- Water based, non toxic and non flammable
- Can be used where potable water is being collected from roofs etc.
- One pack – easily brush or roller applied
- Very durable and highly flexible to withstand movement
- Resistant to mould growth
- Excellent adhesion to a wide variety of substrates
- Can be painted over with a water based exterior grade paint

PREPARATION

All substrates should be structurally sound. Properly brush clean the surface ensuring that it is rust free, clean and free from loose material. Rough surfaces and protrusions should be evened out and leveled out appropriately. Fully remove any existing coatings, grease or any other surface contaminants. If there are holes or honeycombing in concrete substrates, fill it with quick patch repair mortar and allow to cure fully before brush applying the waterproofer. Apply proper flexible silicone sealant to fully seal all joints and corners prior to application of this product.

Apply it generously with a brush. Apply a minimum of 2 coats at right angles to each other with a total dry film thickness of 1.5mm.

Let the first coat dry (3 - 4) hours before you apply the second coat. If the areas are to be trafficable apply 3 coats. Allow it to fully cure for 7 days and then do a ponding test to ensure that the waterproofer has been effectively applied. Contact CEMIX technical support if you intend to use this product on large commercial jobs.

MIXING AND APPLICATION

Before applying mix the product in the container with a stirrer.

COVERAGE

2m² per litre—with a minimum thickness of 1.5mm. Two coats at right angles to each other are recommended.

LIMITATIONS

Do not apply if temperatures are below 10 deg C or if humidity is over 85% or if rain is imminent. Substrate should be surface dry and there should be no rising or migratory damp. The coating will delaminate if there is rising damp underneath the applied waterproofing membrane. Do not apply where there is heavy foot traffic or vehicular traffic. Roofs and surfaces should have adequate falls. Not recommended on glazed shiny surfaces, like glass etc. Do not apply in thick coats, instead apply in successive coats, allowing the first one to dry before you apply the next one.

If medical advice is needed, have product container or label at hand.

Read label before use.

Keep out of reach of children.



Scan to see CEMIX videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

ROOF & GUTTER

TECHNICAL DATA

APPLICATION TEMP	5 - 30°C
APPEARANCE	Light Grey Liquid
POTABLE WATER	Suitable
HYDROSTATIC PRESSURE	Not Suitable

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

WARNING

HAZARD STATEMENTS

- Causes mild skin irritation
- Harmful to aquatic life with long lasting effects

PREVENTION

- Avoid release to the environment

RESPONSE

- If skin irritation occurs: Get medical advice/ attention

DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE INFORMATION.



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring