



MORE THAN CONCRETE



TILING SEALANT

COLOURED SILICONE

AVAILABLE COLOURS: BEIGE, IVORY, WHITE, LIGHT GREY, MID GREY, DARK GREY, BLACK

AVAILABLE SIZES: 310ml



SCAN FOR DETAILS

DESCRIPTION

Cemix® COLOURED SILICONE is a flexible sealant for use in joints such as wall and floor joints, tiled surface and bench tops, bath edges, cupboards, splashbacks and movement joints. It has great adhesion with ceramic tiles, glass, enamel, aluminium, granite, porcelain and sanitary acrylics. Suitable for indoor and outdoor use, CEMIX COLOURED SILICONE is waterproof and is suitable for use in a shower recess. Do not use under waterproofing membranes or in continuous immersion applications such as swimming pools.

TYPICAL APPLICATION/USES

Apply at temperatures between 5°C and 40°C.

1. Ensure joints and surfaces are dry, clean and free from grease, soap and water.
2. Maximum joint width is 30mm and depth 15mm. For joints greater than 10mm deep a backing rod should be used. To achieve a neater finish, or when using unglazed porous tiles, mask joint edges with tape.
3. Trim end nozzle to obtain correct bead width and place cartridge in applicator gun.
4. Apply sealant in a steady continuous bead ensuring good contact with both sides of the joint. Tool off with a moistened spatula to finish the joint smoothly before a skin forms (10 mins).
5. While the silicone is still wet, clean off any excess. (If joint edges have been masked, remove tape whilst still wet. If the silicone has dried on the surface, clean with white spiritsolvent to soften the silicone then scrape off with a blade.)
6. Do not paint over the silicone.

CEMIX GUARANTEE

Product is guaranteed for 10 years when installed to manufacturers instructions. The guarantee does not cover

shade variations and efflorescence as these are caused by factors beyond the manufacturers control, including nature of cement, job site conditions, finishing techniques and uneven drying conditions.

foreign matter, release agents and curing compound residue.

SHELF LIFE

24 months when stored in original unopened packaging.

CAUTION

Contact with natural stone, bitumen-based materials and rubber modified adhesives and metals such as brass and copper, may cause discolouration. Not suitable for use in continuous immersion situations such as swimming pools.

TECHNICAL DATA

APPLICATION TEMP	15°C-40°C
APPEARANCE	Coloured Paste
SHELF LIFE	24 months
SKIN FORMING TIME (+23 °C, 50% RH)	Approx. 10-12 min

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

SAFETY

Use in well-ventilated areas. Avoid skin and eye contact. If uncured material makes contact with the eye, flush with clean



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

TILING SEALANT

water for 15 minutes and seek medical advice. In case of skin contact, first wipe skin with a dry cloth then wash with soap and water. If respiratory discomfort is experienced, move to an area for fresh air. If swallowed, drink plenty of water in small portions, do not induce vomiting and seek medical advice. Keep the product out of the reach of children.

Read label before use.
Keep out of reach of children.
If medical advice is needed, have product container or label at hand.

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

INGREDIENTS

Ethyltriacetoxysilane, CAS:17689-77-9, <5%
Polydimethylsiloxane, CAS: 63148-62-9, NotSpec.
Fillers, CAS: NA, NotSpec.
Auxillary substances, CAS:NA, NotSpec.

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this product's packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to its suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION.



CEMIX® PRODUCTS LTD
19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring