



MORE THAN CONCRETE

0800 ASK CEMIX

WATERPROOFING

1/2

POND & TROUGH WATERPROOFER

FLEXIBLE, NON-TOXIC, WATERPROOFING COMPOUND

AVAILABLE SIZES: 2kg, 4kg, 10kg

AVAILABLE COLORS: Black, Blue



READY TO USE



NON FLAMMABLE



WEATHER RESISTANT



UV STABLE



SCAN FOR DETAILS

DESCRIPTION

CEMIX® POND & TROUGH WATERPROOFER is a non toxic, solvent free, waterbased, high performance polyurethane based elastomeric and flexible exterior grade brushable waterproofer with long term UV and weather resistance to exposed and permanently immersed areas. This versatile durable and tough weatherproof coating is able to withstand extreme weather conditions (hot & cold). It is a very user friendly product that can be brush applied and has excellent adhesion to a wide range of substrates like concrete and wood.

TYPICAL APPLICATION/USES

Exterior protective seamless coating for waterproofing/sealing fish ponds, troughs and other water features in permanently immersed situations. It is tough, flexible, UV stable when left exposed.

ADVANTAGES

- Water based, non toxic and non flammable
- Can be used with fish or where potable water is involved
- Safe & easy to apply by brush or roller
- Fast drying
- Very durable and highly flexible to withstand movement
- Resistant to mould growth
- Excellent adhesion to a wide variety of substrates
- Can be painted over with a water based exterior grade paint

PREPARATION

All substrates should be structurally sound. Properly brush clean the surface ensuring that it is rust free, clean and free from loose material. Rough surfaces and protrusions should be evened out and leveled out appropriately. Fully remove any existing coatings, grease or any other surface contaminants.

If there are holes or honeycombing in concrete substrates, fill it with quick patch repair mortar and allow to cure fully before brush applying the waterproofer.

Apply proper flexible silicone sealant to fully seal all joints and corners prior to application of this product. Apply it in thin successive coats with a brush or a roller. Apply a minimum of 2 coats at right angles to each other with a total dry film thickness of 1.5mm. Let the first coat dry (3-4 hours) before you apply the second coat. For heavy duty applications apply 3 coats. Allow it to fully cure for 15 days and then do a ponding test to ensure that the waterproofer has been effectively applied. Contact Cemix technical support if you intend to use this product on large commercial jobs.

MIXING AND APPLICATION

Before applying mix the product in the container with a stirrer.

COVERAGE

2m² per litre – with a minimum thickness of 1.5mm. Two coats at right angles to each other are recommended.

LIMITATIONS

Do not apply if temperatures are below 10°C or if humidity is over 85% or if rain is imminent. Substrate should be surface dry and there should be no rising or migratory damp. The coating will delaminate if there is rising damp underneath the applied waterproofing membrane. Not recommended on glazed shiny surfaces, like glass etc.

STORAGE & SHELF LIFE

Cemix Pond & Trough can be stored in a cool dry area and used within six (6) months.



Scan to see Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring



MORE THAN CONCRETE

POND & TROUGH

CLEANING

Clean all tools with water and brush immediately after use.

TECHNICAL DATA

APPLICATION TEMP	5 - 30°C
APPEARANCE	Blue or black liquid
POTABLE WATER:	Suitable
HYDROSTATIC PRESSURE:	Not Suitable

The data shown above reflects typical results based on laboratory testing under controlled conditions. Reasonable variations may occur on site.

If medical advice is needed, have product container or label at hand.

Read label before use.

Keep out of reach of children.

HAZARD STATEMENTS

- Harmful to aquatic life with long lasting effects

PREVENTION

- Avoid release to the environment

RESPONSE

- Not applicable

STORAGE

- Not applicable

DISPOSAL

- Dispose of contents/container in accordance with local regulations

DISCLAIMER

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it at no cost in accordance with the requirements of the Consumer Guarantees Act.

SCAN QR CODE FOR MORE PRODUCT INFORMATION



CEMIX® PRODUCTS LTD

19 ALFRED STREET ONEHUNGA 1061
AUCKLAND NEW ZEALAND
0800 ASK CEMIX | +64 09 636 1000
WWW.CEMIX.CO.NZ



Twitter/CemixNZ



Facebook/CemixNz



Pintrest/CemixNZ



YouTube/CemixVideos



Scan to see
Cemix videos

Visit Cemix's wide range of products at www.cemix.co.nz

Concrete & Mortars Repairs & Grouts Admixtures Decorative Sealers Waterproofing Tiling & Flooring